NHachment A

Department of Executive Services Facilities Management Division

King County Courthouse South Entrance Renovation Report
King County Ordinance 15333, Section 114

November 2007

Executive Summary

In August of 2006, the King County Council adopted Ordinance 15333. Ordinance 15333 requires a study and review of design options and operations changes for a potential renovation and reopening of the south entrance to the King County Courthouse (KCC). This report identifies the costs and logistical changes of relocating the Courthouse entrance to the historical south entry in conjunction with closure of the current entrances on Third Avenue and Fourth Avenues.

Ordinance 15333, Section 114 identified four specific areas of concern to be addressed within the report:

- "A detailed security staffing and operations evaluation is needed to determine final costs and savings opportunities"; 1
- "A study of public use and the impacts to public access of both the reopened south entrance and the potential closure of the east and west entrances is needed";²
- "Outreach and consultation with all of these groups and the public is needed prior to any final decision about the reopening the south entrance and closing the east and west entrances"; and
- "A detailed study of the identified issues of funding, debt capacity, security and operational impact and access to the courthouse by all branches of King County government and their employees, jurors and the general public is concluded and adopted by the council."

The initial design concept prepared by FMD provided for two screening stations at the renovated south entrance, in concert with closing the Third and Fourth Avenue entrances. The Third and Fourth Avenue doorways would become exit only. The King County Office of Management and Budget (OMB) evaluated this configuration in a 2007 study of the pedestrian traffic utilization of the three existing entrances to the KCC (currently Third Avenue, Fourth Avenue, and the tunnel from the King County Administration Building).

Courthouse Utilization Study

The utilization study results indicated two critical factors in a South Entrance renovation:

• A loss in the present number of street-level screening stations (three) could result in significant lines during peak entry times, and

¹ Ordinance 1533, Section 114 at Paragraph F.

² Id., at Paragraph G.

³ Id., at Paragraph H.

⁴ Id., at Paragraph I.

 Reconfiguration of the current entrances on Third and Fourth Avenues presents potential additional operational costs if court deputies must monitor the exits.

Following review of OMB's utilization study, FMD and King County Sheriff's Office (KCSO) developed an entryway configuration that accommodates three screening stations in the South entrance. Under this configuration, no net loss of the present number of screening stations occurs. Potential operational cost savings resulting from a reduction of the total number of screeners needed to monitor the screening stations is maximized under this configuration. The utilization study is included as **Appendix A** to this report. A diagram of the south entryway featuring three screening stations is included within **Appendix E**.

Staffing and Operations Changes

The KCSO staffing options included in the OMB pedestrian study present alternatives regarding staffing at the Third and Fourth Avenue exits. The Department of Executive Services, Facilities Management Division (FMD) has identified a "sallyport" door that could prevent re-entry into the Courthouse by exiting patrons. However, KCSO staff recommend additional court deputies to monitor these exits. The addition of these staff presents an operational fiscal impact greater than present-day operational costs, independent of other changes. Given these costs, other potential monitoring options (cameras, re-entry alarms, etc.) should be considered for further study.

Loading Dock Alternatives

The KCC loading dock is currently open eight hours a day. The OMB utilization study observed that the use of the loading dock is minimal. Eliminating the loading dock presents potentially significant cost savings in project capital costs and in ongoing operations costs (due to the lack of need for security personnel dedicated to the loading dock). FMD has provided project cost estimates that both provide for a new KCC loading dock and another eliminating the present loading dock without replacement. Total project costs with the inclusion of a new loading dock facility are \$16,800,000 (see Option 3). Total project costs without a new loading dock are \$8,500,000 (see Option 2).

This report contains the response to the study items identified within Ordinance 15333, Section 114:

Appendix A, the utilization study prepared by OMB, addresses the items called out in Ordinance 15333, Section 114 Paragraphs F. and G. regarding public access to the King County Courthouse and the evaluation of changes to security staffing and operations resulting for a renovated and relocated South entrance.

Appendix B contains a report summarizing the outreach to principal user groups of the Courthouse and their responses, as requested in paragraph H.

Appendix C contains life cycle cost analyses of the present project cost for a renovated south entry with and without a new loading dock underneath City Hall park. Together with the utilization study, these analyses provide the financial data called for in paragraph I.

Appendix D contains the Conceptual Design Estimate Summary prepared by consultants The Robinson Company, and CIP Project Cost Estimate Summaries for project costs with and without construction of a new loading dock.

Appendix E contains examples of the "sallyport" exit doors for the current Third and Fourth Avenue entrances and other design development drawings for the project to date.

A. King County Courthouse Utilization Study

In 2007, the King County Office of Management and Budget conducted a study of the pedestrian utilization of the three existing entrances to the King County Courthouse, and the potential changes to pedestrian traffic and security staffing and operations resulting from a relocation of the entrance to the south side of the building. From this, OMB extrapolated the effect on KCSO security staffing levels in four potential options. The lowest cost option resulted in \$265,000 in annual savings in operations costs. The highest cost option resulted in an additional \$123,000 in operations costs.

a. Utilization Study Findings Regarding Pedestrian Access and Public Use Impacts

There are four screening stations at the Courthouse entrances: two at the Third Avenue entrance, and one each at the Fourth Avenue and tunnel⁵ entrances. The utilization study observed the average hourly pedestrian traffic at each of the three Courthouse entrances and the loading dock, resulting in six findings:

- Pedestrian traffic flows in a predictable pattern with peaks between 8:00 and 9:00 A.M. and 12:30 and 1:30 P.M.
- Queues longer than 10 persons are directly related to the pedestrian traffic flow.
- Different scenarios exist regarding the level of use of the tunnel entrance if the Third and Fourth Avenue entrances are closed in favor of a new south entrance.
- The likelihood of long lines forming increases exponentially if the total number of screening stations is reduced below four.
- Four screening stations are required to meet peak pedestrian traffic flows.
- The loading dock is underutilized and should be considered for elimination.

b. South Entrance Configuration

FMD recently developed an entryway configuration that accommodates three screening stations in the South entrance. This configuration would maximize the potential savings that result from a reduction of the total number of screeners needed to monitor the Courthouse screening stations by allowing closure of the Third and Fourth Avenue entrances. In addition, limiting the street ingress to the south entrance maximizes the objectives in revitalizing the area of City Hall Park, by coordinating pedestrian traffic through the park into a single street level entry.

c. Staffing Needs for Entrance Alternatives

Currently, 16 screeners and 5 deputy sheriffs are needed to staff the Courthouse entrances. If the total number of entrances is reduced, efficiencies can be achieved through a reduction in screening station hours. However, there could be a need for additional security staff at the closed 3rd and 4th Avenue exits.

⁵ The tunnel entrance is located in the basement of the King County Administration Building, screening access to the tunnel connecting the King County Courthouse from the Administration Building.

The utilization study produced four options for staffing the reconfigured South Entrance The operational fiscal impact of each of the options within the utilization study highlights two major cost factors:

- Security Levels: The need for additional security has the greatest impact on operational costs. The Sheriff's Office recommends posting staff at the 3rd and 4th Avenue exits. Alternatively, capital equipment (e.g. sallyport doors with security cameras, alarms, etc.) could be installed in lieu of stationed personnel.
- Loading Dock Hours: The hours of loading dock could also impact operational costs. If the loading dock is eliminated, there could be additional savings in staffing costs.

| Table 1. | Operational | Security | Staffing | Options |
|----------|--------------------|----------|-----------------|----------------|
|----------|--------------------|----------|-----------------|----------------|

| | Current Staffing | Option 1 | Option 2 | Option 3 | Option 4 |
|-----------------------|---------------------|--|---|---|--|
| | | Deputies at 3 rd / 4 th Ave Loading Dock | Deputies at 3 rd / 4 th Ave No Loading Dock | No Deputies at 3 rd / 4 th Ave Loading Dock | No Deputies at 3 rd / 4 th Ave No Loading Dock |
| Screeners | 16 | 12 | 11 | 12 | 11 |
| Deputies | 5 | 10 | 9 | 5 | 5 |
| Total Annual Costs | \$1,183,000 | \$1,306,000 | \$1,186,000 | \$971,000 | \$918,000 |
| Fiscal Impact | \$0 | \$123,000 | \$3,000 | (\$212,000) | (\$265,000) |

Based on the utilization study, the primary driver of total annual operational costs is the security used at the exit only doors at the 3rd and 4th Avenue exits.

c. Other Staffing Needs

This analysis did not look at staffing needs outside of entrance security. For example, if the loading dock is eliminated, there could be additional needs for janitorial services to transport garbage out of the Courthouse. These additional needs will need to be considered if the project moves forward without the loading dock.

B. Outreach to Principal User Groups and Public

FMD performed an outreach study seeking comment from principal user groups of the Courthouse. FMD solicited comments from the following groups regarding renovation and relocation of entrances to the South entrance:

- King County Superior Court
- King County District Court
- King County Prosecuting Attorney's Office

- King County Sheriff
- Department of Judicial Administration
- Office of Civil Rights Enforcement
- Pioneer Square Historic Board
- King County Landmarks Board
- King County Bar Association

Restoring the south entrance was supported by all stakeholder groups provided that the level of security is not reduced and the City Hall park is cleaned up. A narrative matrix of responsive stakeholder comments is included in the outreach study, attached as **Appendix B**. General comments from principal users focused upon:

- Ensuring adequate security appropriate to the Courthouse and City Hall park, and
- Providing sufficient ADA access for persons with disabilities, including a
 passenger load/unload zone as close to the entrance as possible. The current zone
 is on Fourth Avenue.
- Retaining the same number of screening stations to prevent excessive wait times to enter the Courthouse.

C. Funding Analysis of South Entry Renovation

FMD applied a life cycle cost analysis to each of the four options within the utilization study, assuming both construction of new loading dock facility and no new loading dock with a project life cycle of 40 years and a discount rate of 7%. Initial costs are reduced \$7.9 million by eliminating the loading dock facility. Under the lowest cost option, additional life cycle costs for a renovated south entry are estimated at \$2.2 million. Under the highest cost option, total life cycle costs equal \$12.3 million

a. Project Capital Cost Estimates

FMD prepared two cost estimate summaries for the project capital costs: one including a new loading dock underneath City Hall Park, accessed by the existing tunnel off of Fourth Avenue at the Jefferson Street right-of-way, and the second without the loading dock. Both cost estimate summaries include the renovation of the south entryway and lobby area, including escalators and ADA elevator.

Total project costs with the inclusion of a new loading dock facility are \$16,800,000 (See Option 3) Total project costs without a new loading dock are \$8,500,000 (See Option 2).

In addition, the project is the recipient of an \$800,000 grant from the Historic County Courthouse Rehabilitation Grant Program of the Washington Trust for Historic Preservation. This grant amounts are applied within the life cycle costs analysis below.

b. Life Cycle Costs Analysis

A life cycle costs analysis was applied to the OMB utilization study options that consolidated the current KCC street entrances into a single south entrance with three monitoring stations. Options 1 and 2 assume that additional security staff will be posted at the 3rd and 4th Avenue exits. Options 2 and 4 assume that a new loading dock will not need to be built.

Table 2. Life Cycle Cost Analysis

| | Option 1 | Option 2 | Option 3 | Option 4 |
|---|---|--|---|---|
| | Deputies at 3rd / 4th Ave 4 Hr. Loading Dock | Deputies at 3rd / 4th Ave No Loading Dock | No Deputies at 3rd / 4th Aven 4 Hr. Loading Dock | No Deputies at 3rd / 4th Ave No Loading Dock |
| 3rd and 4th avenue exit staffing | yes | Yes | no | no |
| 3rd and 4th Avenue Security | - | | | |
| Doors | no | No | yes | yes |
| Loading Dock | 4 | 0 | 4 | 0 |
| Loading Dock Included | yes | No | yes | No |
| Capital Cost Historic Preservation Grant Annual Staffing Cost | \$16,500,000 (\$800,000) \$123,000 | \$8,500,000 (\$800,000) \$3,000 | \$16,900,000 (\$800,000) (\$212,000) | \$8,900,000 (\$800,000) (\$265,000) |
| LCC Capital | \$10,700,000 | \$5,300,000 | \$10,900,000 | \$5,600,000 |
| LCC Security Staffing | \$1,600,000 | \$0 | (\$2,700,000) | (\$3,400,000) |
| Total LCC | \$12,300,000 | \$5,300,000 | \$8,200,000 | \$2,200,000 |
| Debt Financing Annual | \$1,113,954 | \$546,334 | \$1,142,335 | \$574,715 |
| Payments Debt Payments with Staffing | | | | |

Notes:

Capital cost assumes 25 year financing at 5% with 6% interim financing and transaction costs.

LCC Capital costs includes replacement of the elevator and escalators.

Staffing costs assume 3% annual inflation on salaries. Staffing costs do not include increases in janitorial or maintenance costs.

Analysis period is 40 years and use of a 7% real discount rate

Under the highest cost option, total life cycle costs equal \$11.9 million over 40 years. Under Option 4, total life cycle costs for a renovation of the KCC south entrance total \$1.9 million. The primary cost drivers are the level of security staff and the construction of the new loading dock. The operating costs associated with Park administrative control have not been included in the life cycle cost analysis because the operating costs have not been calculated at this stage of the negotiations and the County has not decided whether to take administrative control of the City Hall Park. The operating costs do not include any additional janitorial or maintenance costs that could be associated with the elimination of the KCC loading dock.

c. Financing Issues

The Council Adopted South Entry Motion called for an evaluation of funding considerations including debt capacity, grants, and property sale revenue.

Debt Capacity: The Current Expense fund debt policy limits debt payment levels to 5% of general fund revenue. Debt scheduled to be issued in the next few years will provide financing for the Integrated Security and Jail Health Project, the Elections facility, the Data Center replacement, and the Accountable Business Transformation project. Based on this planned debt issuance the unallocated general find debt capacity is estimated to be approximately \$27 million in 2012 This equates to a 4.65% debt ratio, or 80% of total debt capacity. Taking a longer view, there won't be significant retirement of debt until 2017. Therefore, any unanticipated debt issuances between 2012 and 2017 will put the County at risk of exceeding the debt limit.

There are two other risk factors to consider in the debt capacity projections. First, the Debt Advisory Task Force has recommended that the debt ratio include the Current Expense fund share of the debt payments in the 63/20 financing arrangements. If approved, this policy change would move the Current Expense Fund closer to the debt limit as the Chinook Building debt payments would be included. The Current Expense Fund share of the Chinook Building debt has not been deducted from the \$75 million of remaining capacity pending action on the recommended policy decision.

Second, the County is in varying stages of an unprecedented number of facility master planning efforts. The District Court, Superior Court, King County Sheriff's Office, the Department of Adult and Juvenile Detention and the Health Department will each have a facility master plan. While it is too early to know the combination of projects that may be approved for debt financing it should be noted that, taken together, these projects amount to a total significantly greater than the amount of available debt capacity. In particular, the potential cost of adult detention facility capacity expansion, by itself, will exceed the available debt capacity. Though a proposed voter approved levy may be considered at a later date there are likely to competing levy proposals on the ballot in the

next few years. It may be necessary to use remaining debt capacity to fund capital projects that represent an immediate need.

Grants: The cost analysis table on page 8 indicates the availability of an \$800,000 Historic County Courthouse Rehabilitation Grant Program of the Washington Trust for Historic Preservation. This grant has been awarded on a reimbursement basis and specifies specific project costs that have been included in the project cost estimates.

Property Sales: At the time of the Courthouse Lobby project approval in 2003 there were two district court sales pending. This \$2.3 million of Current Expense fund property sale proceeds was earmarked to provide revenue backing for a share of the \$6.7 million of project costs. In August of 2007 the Executive proposed the sale of the Kingdome North Lot. Though the sale remains in negotiation, it is estimated that the net sale proceeds could be approximately \$8.8 million after adjustments for transaction costs and the 10% transfer to the Cultural Development Authority. The North Lot transmittal letter recommended that the sale proceeds be reserved in the Current Expense fund to address the potential capital projects listed in the August 2007 transmittal letter excerpt shown below:

"Yesler/Courthouse Campus Current Expense Reserve

The almost ten million dollars in net proceeds provides King County with several unique and unprecedented opportunities to transform the sometimes troubled Yesler/City Hall Park area into a thriving and vibrant gateway to Pioneer Square and the North Lot development.

There are many important Executive and County Council initiatives in or around the Courthouse campus that are in various stages of analysis and implementation. These include:

- Securing development rights or title to properties immediately west of the New County Office Building;
- Potential housing, and redevelopment/improvement of the Courthouse campus itself, either on Goat Hill or in the Yesler area;
- Restoring a new south entrance to the Courthouse and linked improvements to City Hall Park;
- Replacing the existing King County Administration Building with a modern new office tower; and
- Removing the sky bridge from the jail to the Courthouse.

These options continue and support the initiatives set in motion with the development of the North Half Lot for making downtown a more livable and family friendly community.

These options also preserve and enhance King County government services and real property investments in the downtown core.

As a result of our conversations with multiple parties such as the City of Seattle, the Seattle Housing Authority, private developers and others, it has become clear that each of these projects might be linked in ways that benefit all of them. For example, the public benefits of the potential housing projects and City Hall Park improvements may grant us more square footage in a new office tower, which in turn may allow us to generate sufficient revenues to restore the south entrance to the Courthouse or remove the sky bridge.

It is too soon to say exactly how they may all fit together, but what is clear is that this ten million dollars can be a catalyst for one or all of these projects. We should not lose this incredible opportunity by spending the money elsewhere, but rather set the proceeds aside until a clear path for achieving these multiple objectives is reached by both the council and the Executive."

The use of North Lot sale proceeds for the Courthouse South Entrance project could be contingent upon 1.) the successful conclusion of the sale negotiations, and 2.) a commitment by the City of Seattle to make park improvements.

D. Issues to Consider

a. KCC Loading Dock Elimination

Presently, the KCC loading dock is open eight hours a day. Relocation of a KCC loading dock from its present location at the south entrance would require that a new facility be built underground (at the terminus of the existing access tunnel from Fourth Avenue). If the loading dock were eliminated, screening of delivery packages could be performed remotely at the other county buildings during off peak hours. Large deliveries could continue to be facilitated through the Fourth Avenue entrance and scheduled after normal business hours (as is current practice). Trash and recycling material from the Courthouse can be transported via the existing inter-building tunnel system for processing in the Chinook Building (this tunnel is currently used to transport trash/recycling material from the Administration Building to the current loading dock). FMD's analysis demonstrates that the elimination of the loading dock would greatly reduce capital and operations costs.

While the cost savings associated with eliminating the KCC loading dock are large, the relationship of the KCC loading dock and the New Administration building must be understood. If a New Administration building is built, the lack of a loading dock at KCC can be easily and efficiently accommodated by the new building. However, if the New Administration Building is not constructed, there will be operational impacts such as trash handling to be addressed due to the lack of a loading dock at the KCC. In addition, future circumstances could create increased demand for traditional loading dock services. For example, if there is a substantial remodel of the KCC for CID, the PAO or Superior

Court, there might be significant operational impacts to the daily operations without a KCC loading dock.

b. New Security Equipment

The current capital cost estimate includes new security screening equipment that is of greater efficiency then the machines presently in use at the KCC. The new south entrance will utilize state of the art security screening equipment technologies that can improve staffing operations efficiency and pedestrian traffic flow. These improvements include flat screen monitors greeting the public upon entry, broadcasting short video instructions about how to proceed efficiently through the screening process. New walk through metal detectors will be sized for ADA passage, while packages, bags, keys, etc. will be x-rayed using smaller machines with longer rollout tables on each end. The longer tables, particularly at the exit end, will speed retrieval of items by providing space for more than a single person at a time.

This equipment, and other available equipment options, could potentially eliminate the need for three security stations at the south entrance, based on more efficient pedestrian movement through the security check. For example, a Millimeter Wave unit is an entirely new technology that identifies objects and locations on a person's body – eliminating the need for repeat trips through the metal detector. In addition, video observation and equipment interconnectivity could allow a single security officer to monitor all three stations from a single station point. KCSO should be engaged to take an active part in review of new equipment to maximize potential efficiencies in pedestrian traffic and operations.

c. Elevator Modifications to the Courthouse First Floor:

As currently designed, the planned staircase from the South Entrance down to the first floor will require removal of two elevator entries on the south side of the floor. The staircase will not require removal of elevators entries on the second floor. In the proposed elevator configuration it is likely that the majority of individuals entering the South Entrance will take the escalators to the second floor to enter the elevator compartments. The escalators will impact conference room and hallway space on the south side of the Courthouse second floor.

The new ADA elevator that can be entered at the South Entrance to travel to the first and second floor will remove square footage currently used by the food concession area on the first floor.

King County Courthouse South Entrance Renovation Report

Attachment A: King County Office of Management and Budget

Courthouse South Entry Renovation Project

• Courthouse Utilization Study

Courthouse Utilization Study

Summary

In 2007, the King County Office of Management and Budget conducted a study of pedestrian utilization of the King County Courthouse entrances to inform decision-making regarding the potential renovation and reopening of the South Entrance. The goal of the study was to determine whether efficiencies could be achieved by reducing the total number of entrances to the Courthouse from three to two.

Major Findings

- The King County Courthouse requires four full screening stations to accommodate foot traffic during peak hours. If there are fewer than four stations, long lines will occur more frequently during peak hours.
- Efficiencies can be gained if the four stations are consolidated into two entrances. (Currently, four stations are spread over three entrances.)
- OMB identified four staffing options. The highest cost option produced \$123,000 in additional annual costs. The lowest cost option produced \$265,000 in annual savings.
- The operational costs of the security staffing options vary based on the level of security and the hours of the loading dock. Options 1 and 2 assume that court deputies must be stationed at the 3rd Avenue and 4th Avenue exits. This assumption increases the cost of securing the building. Options 1 and 3 assume that the KCCH loading dock operates four hours per day. Options 2 and 4 assume that the loading dock is eliminated and does not require security staffing.¹

| | Current Option 1 Staffing | | Option 2 | Option 3 | Option 4 | |
|-----------------------|---------------------------------------|--|---|---|--|--|
| | , , , , , , , , , , , , , , , , , , , | Deputies at 3 rd / 4 th Ave Loading Dock | Deputies at 3 rd / 4 th Ave No Loading Dock | No Deputies at 3 rd / 4 th Ave Loading Dock | No Deputies at 3 rd / 4 th Ave No Loading Dock | |
| Screeners | 16 | 12 | 11 | 12 | 11 | |
| Deputies | 5 | 10 | 9 | 5 | 5 | |
| Total Annual Costs | \$1,183,000 | \$1,306,000 | \$1,186,000 | \$971,000 | \$918,000 | |
| Fiscal Impact | \$0 | \$123,000 | \$3,000 | (\$212,000) | (\$265,000) | |

¹ These options only considered security costs. This study did not include operational costs associated with building maintenance.

1

Introduction

In 2007, the King County Office of Management and Budget conducted a study of traffic patterns at the King County Courthouse to inform decision-making regarding the potential renovation and reopening of the South Entrance. The goal of the study was to determine whether efficiencies could be achieved by reducing the number of entrances from three to two. This report documents the major findings of this study.

The King County Courthouse currently has three entrances which are located at Third Avenue, Fourth Avenue, and the Tunnel to the Administration Building. The Third Avenue entrance has two full screening stations which are both opened during peak hours. The Fourth Avenue and Tunnel entrances each have one full screening station. The screening stations include an X-Ray machine to scan personal belongings and a Magnetometer. Current security protocols mandate that all personal effects must be screened.

I. Traffic Study

Traffic data was collected during the months of July and August. Traffic counts were taken at each entrance for each hour of the day on every day of the week. The count was recorded at fifteen minute increments. Additionally, OMB took note of the number of times that a queue formed with more than 10 individuals. Detailed information on the counts can be found in Appendix A.

Finding #1: Traffic flows in a predictable pattern with peaks occurring between 8:00 and 9:00 A.M. and 12:30 and 1:30 P.M. (See Table 1.)






Table 1 shows the average traffic count per hour at each entrance. The highest traffic counts occurred at Third Avenue while the lowest counts occurred at the tunnel.

Finding #2: The formation of queues greater than 10 is strongly associated with the amount of traffic coming through the doors.

Table 2 shows the average number of queues over ten that occurred at the Fourth Avenue entrance. Between two and three queues occurred at this entrance during the peak traffic hours. Similar trends can be observed at the Third Avenue entrance (see Table 3). Long lines were not observed at the tunnel entrance.





Finding #3: If the Third and Fourth Avenue entrances are closed, the traffic from those entrances will most likely be diverted to the South Entrance. However, some of the overflow could be diverted to the Tunnel.

OMB used the data collected to evaluate the operational impact of closing the Third and Fourth Avenue entrances and reopening the South Entrance. Two scenarios were developed to predict the likely flow of traffic at the South Entrance. Under the first scenario, all of the traffic from the closed Third and Fourth Avenue entrances would flow to the South Entrance. Under the second scenario, two thirds of the building traffic would flow to the South Entrance and one third would flow to the tunnel. These scenarios represent two extremes. It is likely that some individuals entering from street level will use the tunnel if they notice long queues forming at the South Entrance. Others may be unfamiliar with the Tunnel entrance and could choose to remain at the South Entrance.

Table 4. Two Scenarios of Traffic Flow


| | Scenario One: | | Scenario Two: | |
|-------|-------------------|--------|-----------------------|--------|
| | High Traffic Flow | w to | Lower Traffic Flow to | |
| | South Entrance | | South Entrance | |
| Hour | South Entrance | Tunnel | South Entrance | Tunnel |
| 6:00 | 138 | 39 | 118 | 58 |
| 7:00 | 501 | 94 | 399 | 196 |
| 8:00 | 1,061 | 125 | 795 | 391 |
| 9:00 | 549 | 80 | 421 | 207 |
| 10:00 | 483 | 73 | 372 | . 183 |
| 11:00 | 380 | 59 | 295 | 145 |
| 12:00 | 689 | 78 | 514 | 253 |
| 13:00 | 928 | 68 | 667 | 329 |
| 14:00 | 388 | 75 | . 310 | 153 |
| 15:00 | 304 | 53 | 239 | 118 |
| 16:00 | 163 | 22 | 124 | 61 |
| 17:00 | 51 | 10 | 41 | 20 |

These decisions will be influenced by the screening capacity available at each entrance. Currently, there are four screening stations available at the three entrances. To accommodate the traffic under Scenario One, three screening stations would need to be available at the South Entrance and one station would need to be available at the Tunnel.

To determine the operational impact of these scenarios, OMB built a model that described the relationship between increases in the amount of traffic per screening stations and the probability of a queue forming (see Table 5).² This model was used to predict the likelihood of queues given variation in the number of screening stations.

4

² Traffic counts per station were rounded to the nearest twenty. The probability of a line forming was calculated for each group of twenty and graphed in Table 5. An exponential function was fit to the data that describes the relationship between the traffic per station and the probability of a line forming.



Finding #5: The likelihood of queues forming will more than double if the total number of screening stations is reduced.

OMB used the traffic model in Table 5 to determine the likelihood of long lines forming at the South Entrance during peak hours. The model was tested on four scenarios:

- Scenario 1A assumes that all of the traffic from the Third and Fourth entrance will flow to the South Entrance, the tunnel traffic will remain unchanged, three screening stations will be available at the South Entrance, and one station will be available at the tunnel.
- Scenario 1B assumes that all of the traffic from the Third and Fourth entrance will flow to the South Entrance, the tunnel traffic will remain unchanged, two screening stations will be available at the South Entrance, and one station will be available at the tunnel.
- Scenario 2A assumes that two thirds of the building traffic will flow to the South Entrance, one third of the traffic will flow to the tunnel, three screening stations will be available at the South Entrance, and one station will be available at the tunnel.
- Scenario 2B assumes that two thirds of the building traffic will flow to the South Entrance, one third of the traffic will flow to the tunnel, two screening stations will be available at the South Entrance, and one station will be available at the tunnel.

Table 6 shows the probability of a line forming between 8:00 and 9:00 A.M for the scenarios that assume no traffic is diverted to the tunnel (1A and 1B). Both of these scenarios assume high traffic flows. However, Scenario 1A assumes three stations are open and Scenario 1B assumes two stations are open. With fewer stations available, the likelihood a line forming increases by 261%. For example, with three stations open, there is a 36% chance of a queue forming between 8:30 and 8:45. If the number of stations is reduced to two, the likelihood of a line forming increases to 93%.





Table 7 shows Scenarios 2A and 2B that assume that some of the traffic can be diverted to the tunnel. Given the lower traffic levels, the overall likelihood of a line forming is lower than the high traffic scenarios. However, reducing the number of stations still has an impact on queuing.

It should be noted that these scenarios are based on data from summer traffic counts. The total traffic flow is likely to increase in the fall and winter when a greater number of court cases are active. For this reason, the higher traffic scenario is a better source of information for planning purposes.




Finding #6: Four screening stations are required to meet the demands of traffic flow during peak hours.

To maintain the current level of service, at least four screening stations should be available during peak hours. Having four stations will reduce the likelihood of long lines.

Finding #7: Traffic flows at the Loading Dock are very low. FMD should determine whether the loading dock could be eliminated.

OMB also counted the number of entrants to the loading dock. The total volume averaged 37 per day. The County should consider the cost effectiveness of operating the loading dock. FMD, in consultation with the Sheriff, should determine whether freight shipments could be delivered at other County buildings and transmitted to the Courthouse via the tunnels.



II. Analysis of Staffing Options

OMB used the findings of the traffic study to estimate the operational costs of the South Entrance project. Currently, King County spends approximately \$1.2 million to staff the security stations at each entrance. These entrances are staffed by approximately 16 weapons screeners and 5 court deputies.³ Reconfiguring the entrances will undoubtedly alter the amount of security staffing required and could increase or decrease the total operational costs.

OMB developed a range of staffing options to accommodate the expected levels of traffic at a reopened South Entrance. The options were designed to optimize the number of screening stations available at different hours of the day. Details on each option can be found in Appendix B.

The four options discussed in this section vary based on security needs and the hours of the loading dock.

Security Needs: The Sheriff's Office expressed concern that converting the Third and Fourth Avenue entrances to exit only doors could create security risks. The Sheriff's Office recommended staffing the exit only doors with court deputies. These additional staffing needs increase the cost of securing the building. Alternatively, capital equipment (e.g. sallyport doors, cameras, alarms, etc.) could be installed in lieu of stationed personnel.

In May 2007, a study of Courthouse security was conducted by the U.S. Marshal Service. The study recommended increasing the level of security staff in the Courthouse. These recommendations were not included in the options developed for this report. OMB only considered security needs that were directly related to the reconfiguration of the entryways.

Loading Dock: Currently, the loading dock is open eight hours a day. The traffic study demonstrated that the loading dock only received 37 entrants per day. This has led OMB to conclude that the hours could be reduced to optimize efficiency. Further efficiencies could be achieved if the loading dock were eliminated altogether. In this case, deliveries would need to be scheduled for off-peak hours and delivered via the tunnel entrance.

Options 1 and 2 assume that court deputies will be placed at the closed street level entrances (see Table 9). These options are the most expensive alternatives. Options 1 and 3 assume that the loading dock will operate four hours a day. Options 2 and 4 assume that the loading dock is eliminated.

³ These estimates do not include supervisors.

Table 9. Operational Fiscal Impact of Staffing Courthouse Entrances

| | Current Staffing | Option 1 | Option 2 | Option 3 | Option 4 | |
|-----------------------|---------------------|--|---|---|--|--|
| | | Deputies at 3 rd / 4 th Ave Loading Dock | Deputies at 3 rd / 4 th Ave No Loading Dock | No Deputies at $3^{rd} / 4^{th}$ Ave Loading Dock | No Deputies at 3 rd / 4 th Ave No Loading Dock | |
| Screeners | 16 | 12 | 11 | 12 | 11 | |
| Deputies | 5 | 10 | 9 | 5 | 5 | |
| Total Annual Costs | \$1,183,000 | \$1,306,000 | \$1,186,000 | \$971,000 | \$918,000 | |
| Fiscal Impact | \$0 | \$123,000 | \$3,000 | (\$212,000) | (\$265,000) | |

Note: These options represent an approximation of costs. Staffing level and scheduling considerations could create constraints which could increase or decrease estimates.

These options only consider the costs of securing each entrance and does not include changes in building maintenance costs. For example, if the loading dock is eliminated, there could be additional needs for janitorial services to transport garbage out of the Courthouse. These additional needs will need to be considered if the project moves forward without the loading dock.

Other Considerations: The traffic study demonstrates that the Courthouse requires four security stations during peak traffic hours. The options developed assume that three of these stations could be accommodated in the South Entrance. The Sheriff's Office has expressed concern that the high level of traffic coming through three stations could create confusion and pose a security risk.

If the South Entrance is not equipped with three stations, the County could develop a strategy to divert a large share of the street level traffic to the tunnel. Under this scenario, a second screening station could be moved to the Tunnel to accommodate the increase in traffic during peak hours. This alternative configuration would not alter the cost estimates developed in Table 9. Additionally, FMD and the Sheriff's Office could develop process improvements that speed the flow of traffic through the screening stations. If these strategies are not successful, the County may need to open the Third or Fourth Avenue entrance to accommodate the extra traffic. This would add to the operational costs of the project. Alternatively, the County could accept long queues during peak hours.

Conclusion

OMB has developed a range of cost estimates for staffing the secured entryways to the Courthouse. The highest cost option would add \$123,000 in annual operational costs. The lowest cost option could produce \$265,000 in savings. The range in costs is primarily dependent on the level of security provided at the entryways.

Table 10. Assumptions Used to Develop Options

| | Option 1 | Option 2 | Option 3 | Option 4 | | |
|--------------------------------------|--|---|---|--|--|--|
| | Deputies at 3 rd / 4 th Ave Loading Dock | Deputies at 3 rd / 4 th Ave No Loading Dock | No Deputies at 3 rd / 4 th Ave Loading Dock | No Deputies at 3 rd / 4 th Ave No Loading Dock | | |
| | Securit | y Considerations | | | | |
| Enhanced Security on Loading Dock | Yes | No | No | No | | |
| Enhanced Security on Exits | Yes | Yes | No | No | | |
| | Number of Screen | ning Stations per E | ntrance | | | |
| South Entrance | 3 Stations | 3 Stations | 3 Stations | 3 Stations | | |
| Tunnel | 1 Station | 1 Station | 1 Station | 1 Station | | |
| 3rd Ave | Exit Only | Exit Only | Exit Only | Exit Only | | |
| 4th Ave | Exit Only | Exit Only | Exit Only | Exit Only | | |
| Operational Hours | | | | | | |
| Loading Dock Hours | 4 | 0 | 4 | 0 | | |
| South Entrance | 12 | 12 | 12 | 12 | | |
| Tunnel | 12 | 12 | 12 | 12 | | |

Appendix A. Daily Traffic Counts

Third Avenue Entrance

| Hour | Monday | Tuesday | Wednesday | Thursday | Friday | Total |
|-------|--------|---------|-----------|----------|--------|-------|
| 6:00 | 70 | 71 | 67 | 77 | 53 | 338 |
| 7:00 | 355 | 279 | 358 | 240 | 206 | 1438 |
| 8:00 | 572 | 774 | 584 | 551 | 489 | 2970 |
| 9:00 | 293 | 270 | 334 | 311 | 323 | 1531 |
| 10:00 | 348 | 329 | 194 | 321 | 246 | 1438 |
| 11:00 | 233 | 218 | 215 | 239 | 238 | 1143 |
| 12:00 | 521 | 454 | 377 | 387 | 289 | 2028 |
| 13:00 | 589 | 611 | 667 | 617 | 411 | 2895 |
| 14:00 | 237 | 210 | 201 | 261 | 198 | 1107 |
| 15:00 | 186 | 161 | 196 | 155 | 180 | 878 |
| 16:00 | 109 | 74 | 87 | 110 | 85 | 465 |
| 17:00 | 38 | 18 | 28 | 34 | 38 | 156 |
| Total | 3551 | 3469 | 3308 | 3303 | 2756 | 16387 |

Fourth Avenue Entrance

| Hour | Monday | Tuesday | Wednesday | Thursday | Friday | Total |
|-------|--------|---------|-----------|----------|--------|-------|
| 6:00 | 80 | 76 | 81 | 66 | 47 | 350 |
| 7:00 | 248 | 222 | 230 | 197 | 172 | 1069 |
| 8:00 | 452 | 548 | 519 | 471 | 345 | 2335 |
| 9:00 | 236 | 282 | 237 | 229 | 230 | 1214 |
| 10:00 | 202 | 187 | 187 | 212 | 188 | 976 |
| 11:00 | 168 | 139 | 168 | 157 | 126 | 758 |
| 12:00 | 307 | 281 | 324 | 314 | 192 | 1418 |
| 13:00 | 392 | 327 | 335 | 405 | 287 | 1746 |
| 14:00 | 172 | 124 | 181 | 168 | 190 | 835 |
| 15:00 | 141 | 125 | 148 | 109 | 117 | 640 |
| 16:00 | 72 | 59 | 90 | 73 | 55 | 349 |
| 17:00 | 26 | 5 | 10 | 49 | 9 | 99 |
| Total | 2496 | 2375 | 2510 | 2450 | 1958 | 11789 |

Tunnel Entrance

| Hour | Monday | Tuesday | Wednesday | Thursday | Friday | Total |
|-------|--------|---------|-----------|----------|--------|-------|
| 6:00 | 54 | 45 | 46 | 38 | 12 | 195 |
| 7:00 | 113 | 91 | 106 | 79 | 80 | 469 |
| 8:00 | 118 | 142 | 156 | 131 | 79 | 626 |
| 9:00 | 69 | 80 | 75 | 100 | 74 | 398 |
| 10:00 | 78 | 81 | 66 | 81 | 59 | 365 |
| 11:00 | 55 | 58 | 55 | 49 | 80 | 297 |
| 12:00 | 63 | 87 | 69 | 69 | 104 | 392 |
| 13:00 | 84 | 68 | 48 | 53 | 85 | 338 |
| 14:00 | 77 | 69 | 96 | 62 | 69 | 373 |
| 15:00 | 43 | 67 | 56 | 64 | 34 | 264 |
| 16:00 | 14 | 24 | 31 | 26 | 15 | 110 |
| 17:00 | 9 | 16 | 7 | 13 | 5 | 50 |
| Total | 777 | 828 | 811 | 765 | 696 | 3877 |

Loading Dock

| | Monday | Tuesday | Wednesday | Thursday | Friday | Total |
|-------|--------|---------|-----------|----------|--------|-------|
| 8:00 | 1 | 2 | 11 | 4 | 5 | 23 |
| 9:00 | 7 | 2 | 1 | 1 | 5 | 16 |
| 10:00 | 12 | 4 | 1 | 8 | 5 | 30 |
| 11:00 | 6 | 3 | 1 | 8 | 5 | 23 |
| 12:00 | 11 | 8 | 3 | 5 | 14 | 41 |
| 13:00 | 10 | 7 | 2 | 1 | 9 | 29 |
| 14:00 | 1 | 2 | 3 | 1 | 1 | 8 |
| 15:00 | 0 | 5 | 1 | 4 | 3 | 13 |
| | 48 | 33 | 23 | 32 | 47 | 183 |

Appendix B. Detailed Staffing Options

KEY ASSUMPTIONS

| Extra Staff on Exits | SeX |
|---------------------------|------------|
| Loading Dock (L.D.) Hours | 4 |
| Tunnel | 1 Station |
| 4th Ave | Exit Only |
| 3rd Ave | Exit Only |
| South Entrance (S.E.) | 3 Stations |

WEAPONS SCREENERS

| Current Staffing | ing | | | | | | Proposed Staffing | taffing | | | | | | | ſ | Difference |
|------------------|---------|---------|-------|--------|-------|--------|-------------------|---------|-----|-------|-------|-------|--------|-------|--------|----------------|
| | 3rd - A | 3rd - B | 4th | Tunnel | L.D. | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 9.00 | Э | | 2 | - | | 9 | | | | 3 | | | 1 | | 4 | (2) |
| 7.00 | ю | ဗ | ဗ | 2 | | 5 | | | | က | ღ | | 7 | | 80 | <u>(c)</u> |
| 8.00 | က | 9 | ဗ | 2 | - | 12 | | | | က | ღ | က | 7 | | 7 | (3 |
| 00.6 | ю | 9 | ဗ | 2 | - | 12 | | | | က | ღ | က | 7 | | = | £) |
| 10.00 | ю | 9 | ဗ | 2 | - | 12 | | | | က | ღ | | 7 | - | 6 | (3) |
| 11.00 | ო | ဗ | ဗ | 2 | - | 12 | | | | ဗ | ღ | | 7 | - | თ | (3) |
| 12.00 | ю | ဗ | ဗ | 2 | - | 12 | | | | ღ | ო | က | 2 | | = | (1) |
| 13.00 | ю | ဗ | က | 2 | - | 12 | | | | က | ო | | 7 | - | თ | (3) |
| 14.00 | ღ | ဗ | ဗ | 2 | - | 12 | | | | က | ო | | 7 | - | 6 | <u>(S)</u> |
| 15.00 | က | | က | 2 | - | 6 | | | | က | | | 7 | | ည | (4) |
| 16.00 | က | | က | 2 | | 8 | | | | က | | | 7 | | 2 | <u>(S)</u> |
| 17.00 | ဗ | | 2 | - | | 9 | | | | 3 | | | 1 | | 4 | (2) |
| Total Hrs | 98 | 24 | 34 | 22 | 8 | 124 | 0 | 0 | 0 | 36 | 24 | 6 | 22 | 4 | 92 | (53) |
| Annual Hrs | 000'6 | 6,000 | 8,500 | 5,500 | 2,000 | 31,000 | ı | | • | 000'6 | 6,000 | 2,250 | 5,500 | 1,000 | 23,750 | (7,250) |
| FTEs | | | | | | 16.0 | | | | | | | | | 12.0 | (4.0) |

COURT DEPUTIES

| Current Staffing | Buj | | | | | | Proposed Staffing | affing | | | | | | | ַ | Difference |
|------------------|---------|---------|-------|--------|------|--------|-------------------|---------|-------|-------|-------|-------|--------|-------|--------|------------|
| | 3rd - A | 3rd - B | 4th | Tunnel | L.D. | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 90.9 | - | | - | - | | 3 | - | | - | 1 | T. | | - | | 5 | 2 |
| 7.00 | - | | - | - | | ო | - | | - | - | - | | - | | 2 | 7 |
| 8.00 | 2 | | 7 | - | | ις | 2 | | - | - | - | 7 | - | - | 60 | ဂ |
| 9.00 | 7 | | 2 | - | | ß | 2 | | - | - | - | 2 | - | | 80 | က |
| 10.00 | - | | - | - | | m | - | | - | - | - | | - | 7 | 7 | 4 |
| 11.00 | - | | - | - | | က | - | | - | - | - | | - | 7 | 7 | 4 |
| 12.00 | - | | - | - | | e | - | | - | - | - | 7 | - | | | 4 |
| 13.00 | 7 | | 2 | - | | 5 | 7 | | - | - | - | | - | 7 | 80 | က |
| 14.00 | - | | _ | - | | ю | - | | - | - | - | | - | 7 | 7 | 4 |
| 15.00 | - | | - | - | | က | - | | - | - | - | | - | | လ | 2 |
| 16.00 | - | | - | - | | ო | - | | - | - | - | | - | | S | 2 |
| 17.00 | 1 | | 1 | 1 | | 3 | - | | 1 | 1 | - | | - | | 2 | 2 |
| Total Hrs | 15 | 0 | 15 | 12 | 0 | 42 | 15 | 0 | 12 | 12 | 12 | 9 | 12 | 8 | 11 | 35 |
| Annual Hrs | 3,750 | • | 3,750 | 3,000 | • | 10,500 | 3,750 | 1 | 3,000 | 3,000 | 3,000 | 1,500 | 3,000 | 2,000 | 19,250 | 8,750 |
| FTEs | | | | | | 5.0 | | | | | | | | | 10.0 | 5.0 |

| Current Staffing | | | | Proposed Staffing | | | | Difference | e | | |
|--------------------|----------|------|-------------|--------------------|----------|------|-------------|------------|-----------|------|------------|
| | FTE Cost | FTEs | Total Cost | | FTE Cost | FTEs | Total Cost | | | FTEs | Total Cost |
| Security Screeners | \$53,000 | 16 | \$848,000 | Security Screeners | \$53,000 | 12 | \$636,000 | Security | Screeners | (4) | (212,000) |
| Deputies | \$67,000 | 5 | \$335,000 | Deputies | \$67,000 | 10 | \$670,000 | Deputies | | 5 | 335,000 |
| Total Cost | | | \$1,183,000 | Total Cost | | | \$1,306,000 | Total Cost | st | | 123,000 |
| | | | | | | | | | | | |

KEY ASSUMPTIONS

| Extra Staff on Exits | Yes |
|---------------------------|------------|
| Loading Dock (L.D.) Hours | 0 |
| Tunnel | 1 Station |
| 4th Ave | Exit Only |
| 3rd Ave | Exit Only |
| South Entrance (S.E.) | 3 Stations |

WEAPONS SCREENERS

| Current Staffing | ing | | | | | Ē | Proposed Staffing | taffing | | | | | | | Ī | Difference |
|------------------|---------|---------|-------|--------|-------|--------|-------------------|---------|-----|-------|-------|-------|--------|------|--------|------------|
| | 3rd - A | 3rd - B | 4th | Tunnel | L.D. | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 00'9 | 3 | | 2 | 1 | | 9 | | | | င | | | - | | 4 | (2) |
| 7.00 | က | | က | 2 | | 80 | | | | ო | က | | 7 | | 60 | • |
| 8.00 | ღ | ღ | ဗ | 2 | - | 12 | | | | က | ო | ო | 7 | | + | (3) |
| 9.00 | ღ | ო | ღ | 7 | - | 12 | | | | က | က | ღ | 7 | • | Ξ | 3 |
| 10.00 | ო | ო | ო | 2 | - | 12 | | | | က | ო | | 7 | | 00 | 4) |
| 11.00 | ო | ღ | ღ | 7 | - | 12 | | | | ო | ო | | 7 | | 80 | 4) |
| 12.00 | ო | ო | က | 7 | - | 12 | | | | ღ | ო | | 7 | | 60 | (4) |
| 13.00 | က | ო | က | 7 | - | 12 | | | | က | ო | ო | 7 | | Ξ | 3 |
| 14.00 | ო | ღ | က | 7 | - | 12 | | | | က | ო | | 7 | | 60 | (4) |
| 15.00 | ന | ო | က | 7 | - | 12 | | | | က | | | 7 | | c, | <u>(2</u> |
| 16.00 | ო | | က | 8 | | æ | | | | က | | | 7 | | S | (3) |
| 17.00 | ဗ | | 2 | 1 | | 9 | | | | 3 | | | - | | 4 | (2) |
| Total Hrs | 36 | 24 | 34 | 22 | 8 | 124 | 0 | 0 | 0 | 36 | 24 | თ | 22 | 0 | 91 | (33) |
| Annual Hrs | 000'6 | 6,000 | 8,500 | 5,500 | 2,000 | 31,000 | | • | • | 000'6 | 9'000 | 2,250 | 5,500 | ٠ | 22,750 | (8,250) |
| FTEs | | | | | | 16.0 | | | | | | | | | 11.0 | (5.0) |

COURT DEPUTIES

| Current Staffing | 2 | | | | | | Proposed Staffing | affino | | | | | | | - | Difference |
|------------------|--------------|---------|-------|--------|------|--------|-------------------|---------|-------|-------|-------|-------|--------|------|--------|------------|
| | 3rd - A | 3rd - B | 4th | Tunnel | L.D. | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 00'9 | - | | ۳ | - | | 3 | 1 | | ۲. | - | 1 | | 1 | | 2 | 2 |
| 7.00 | - | | - | - | | က | - | | - | - | - | | - | | ß | 7 |
| 8.00 | 7 | | 2 | - | | ß | - | | - | - | - | 7 | - | | 7 | 2 |
| 9.00 | 7 | | 2 | - | | S | - | - | - | - | - | 7 | - | | 00 | ю |
| 10.00 | - | | - | - | | က | - | - | - | - | - | | - | | g | က |
| 11.00 | - | | - | - | | က | - | | - | - | - | | - | | 5 | 2 |
| 12.00 | - | | - | - | | ო | - | | - | - | - | | - | | ß | 2 |
| 13.00 | 7 | | 7 | - | | 5 | - | - | - | - | - | 7 | - | | 80 | ო |
| 14.00 | - | | - | - | | က | - | | - | - | - | | - | | ß | 2 |
| 15.00 | - | | - | - | | က | - | | - | - | - | | - | | ς. | 2 |
| 16.00 | - | | - | - | | က | - | | - | - | - | | - | | ις. | 2 |
| 17.00 | - | | 1 | 1 | | 3 | 1 | | 1 | 1 | 1 | | 1 | | 2 | 2 |
| Total Hrs | 15 | 0 | 15 | 12 | 0 | 42 | 12 | 3 | 12 | 12 | 12 | 9 | 12 | 0 | 69 | 27 |
| Annual Hrs | 3,750 | • | 3,750 | 3,000 | • | 10,500 | 3,000 | 750 | 3,000 | 3,000 | 3,000 | 1,500 | 3,000 | ٠ | 17,250 | 6,750 |
| FTEs | | | | | | 5.0 | | | | | | | | | 9.0 | 4.0 |

| Current Staffing | | | | Proposed Staffing | | | | Difference | | |
|--------------------|----------|------|-------------|--------------------|----------|------|-------------|--------------------|------|------------|
| | FTE Cost | FTEs | Total Cost | | FTE Cost | FTEs | Total Cost | | FTEs | Total Cost |
| Security Screeners | \$53,000 | 16 | \$848,000 | Security Screeners | \$53,000 | 11 | \$583,000 | Security Screeners | (2) | (265,000) |
| Deputies | \$67,000 | 5 | \$335,000 | Deputies | \$67,000 | 6 | \$603,000 | Deputies | 4 | 268,000 |
| Total Cost | | | \$1,183,000 | Total Cost | | | \$1,186,000 | Total Cost | | 3,000 |
| | | | | | | | | | | |

KEY ASSUMPTIONS

| 3rd Ave |
|-----------|
| |
| Exit Only |

WEAPONS SCREENERS

| | | | | | | ٩ | Drongend Staffing | Gno | | | | | | İ | ٩ | Difference |
|------------------|---------|---------|-------|--------|-------|--------|-------------------|---------|-----|-------|-------|-------|--------|----------|--------|------------|
| Content Stalling | 3rd - A | 3rd - B | ŧ\$ | Tunnel | L.D. | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | ار. ا | Total | |
| 9.00 | | | 2 | - | | 9 | | | | 9 | | | - | | 4 | (2) |
| 7.00 | က | | က | 7 | | 80 | | | | က | | | 7 | | S | (3) |
| 8.00 | e | ო | က | 2 | - | 12 | | | | ო | က | က | 2 | | 7 | (1) |
| 9:00 | က | ო | က | 7 | - | 12 | | | | ო | က | ო | 7 | | 1 | Ξ |
| 10.00 | ღ | ღ | က | 7 | - | 12 | | | | ဗ | က | | 2 | - | o | <u>(c)</u> |
| 11.00 | ო | ю | က | 7 | _ | 12 | | | | က | က | | 7 | - | o | (9) |
| 12.00 | ო | က | က | 7 | _ | 12 | | | | ၈ | က | က | 2 | | 11 | £) |
| 13.00 | ო | က | က | 7 | - | 12 | | | | ღ | ო | | 7 | - | 6 | (3) |
| 14.00 | ო | e | က | 2 | - | 12 | | | | ო | ო | | 7 | - | 6 | (3) |
| 15.00 | ღ | က | က | 7 | - | 12 | | | | ო | ო | | 7 | | 80 | (4) |
| 16.00 | က | | က | 7 | | 80 | | | | ო | | | 7 | | 5 | (3) |
| 17.00 | ღ | | 2 | - | | ဖ | | | | 3 | | | 1 | | 4 | (2) |
| Total Hrs | 36 | 24 | 뚕 | 22 | 8 | 124 | 0 | 0 | 0 | 96 | 24 | თ | 22 | 4 | 92 | (29) |
| Annual Hrs | 000'6 | 6,000 | 8,500 | 5,500 | 2,000 | 31,000 | • | 1 | | 9,000 | 6,000 | 2,250 | 5,500 | 1,000 | 23,750 | (7,250) |
| ETE | | | | | | 16.0 | | | | | | | | | 12.0 | (4.0) |

COURT DEPUTIES

| Current Staffing | | | | | | | Proposed Staffing | ffing | | | | | | | _ | Difference |
|------------------|---------|---------|-------|--------|---|--------|-------------------|---------|-----|-------|-------|-------|--------------|------|--------|------------|
| | 3rd - A | 3rd - B | 4th | Tunnel | ٦ | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 90.9 | ı | | - | 1 | | 3 | | | | - | 1 | | - | | ၈ | • |
| 7.00 | - | | - | - | | က | | | | - | - | | - | | က | • |
| 8.00 | 8 | | 2 | - | • | 2 | | | | - | - | 7 | - | | 2 | • |
| 9.00 | 2 | | 2 | - | | 2 | | | | - | - | 7 | - | | c, | |
| 10.00 | - | | - | - | | က | | | | - | - | | - | | က | • |
| 11.00 | - | | | - | | က | | | | - | - | | - | | ဗ | • |
| 12.00 | - | | - | - | | က | | | | - | - | | - | | က | • |
| 13.00 | 2 | | 7 | - | | ıç, | | | | - | - | 2 | - | | ς | • |
| 14.00 | - | | - | - | | က | | | | - | - | | - | | ၈ | • |
| 15.00 | - | | - | - | | m | | | | - | - | | - | | ო | • |
| 16.00 | - | | - | - | | ო | | | | - | - | | - | | ღ | • |
| 17.00 | - | | - | 1 | | 3 | | | | - | - | | - | | 3 | • |
| Total Hrs | 15 | 0 | 15 | 12 | 0 | 42 | 0 | 0 | 0 | 12 | 12 | 9 | 12 | 0 | 42 | |
| Annual Hrs | 3,750 | | 3,750 | 3,000 | • | 10,500 | • | • | • | 3,000 | 3,000 | 1,500 | 3,000 | | 10,500 | • |
| FTEs | | | | | | 5.0 | | | | | | | | | 5.0 | • |

| Current Staffing | | | | 4 | oposed Staffing | | | | ٥ | ifference | | |
|--------------------|----------|------|-------------|----------|-------------------|----------|------|------------|----------|-------------------|------|------------|
| 0 | FTE Cost | FTEs | Total Cost | L_ _ | | FTE Cost | FTES | Total Cost | _ | | FTEs | Total Cost |
| Security Screeners | \$53,000 | 16 | \$848,000 | S | scurity Screeners | \$53,000 | 12 | \$636,000 | <u> </u> | ecurity Screeners | (4) | (212,000) |
| Deputies | \$67,000 | 5 | \$335,000 | <u> </u> | Deputies | \$67,000 | 5 | \$335,000 | ٥ | Deputies | | |
| Total Cost | | | \$1,183,000 | <u> </u> | otal Cost | | | \$971,000 | Ĺ | otal Cost | | (212,000) |

KEY ASSUMPTIONS

| Tunnel Loading |
|-----------------------------|
| ance (S.E.) 3rd Ave 4th Ave |

WEAPONS SCREENERS

| 37.70 | | | | | | ľ | Pronosed Staffing | 2 | | | | | | | 2 | Difference |
|------------------|---------|---------|-------|--------|------------|--------|-------------------|---------|-----|-------|-------|-------|--------|------|--------|------------|
| Current Stalling | 3rd - A | 3rd - B | 4th | Tunnel | L.D. | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 9 00 | ٣ | | 2 | - | | g g | | | | 3 | | | - | | 4 | (2) |
| 7.00 | · m | | က | 2 | | 60 | | | | ო | | | 2 | | 5 | (9) |
| 8.00 | , m | ო | · ю | . 2 | - | 12 | | | | က | ო | က | 2 | | 7 | 3 |
| 00.6 | ю | ო | က | 7 | * - | 12 | | | | ო | ო | ო | 2 | | 7 | 3 |
| 10.00 | · m | ო | က | 7 | - | 12 | | | | ო | ო | | 2 | | 80 | (4) |
| 11.00 | ю | თ | က | 7 | - | 12 | | | | ო | ო | | 7 | | 80 | (4) |
| 12.00 | · m | ო | ღ | 7 | _ | 12 | | | | ო | ო | | 7 | | 80 | 4) |
| 13.00 | n | ო | ო | 7 | _ | 12 | | | | ო | ო | က | 7 | | Ξ | £ |
| 14.00 | ღ | ო | ო | 7 | _ | 12 | | | | ო | ၈ | | 7 | | 80 | (4) |
| 15.00 | ღ | ო | ო | 7 | - | 12 | | | | ო | ო | | 7 | | 80 | (4) |
| 16.00 | ო | | ო | 8 | | • | | | | က | | | 7 | | s, | (3) |
| 17.00 | က | | 7 | - | | 9 | | | | 3 | | | - | | 4 | (2) |
| Total Hrs | 36 | 24 | 34 | 22 | 80 | 124 | 0 | 0 | 0 | 36 | 24 | თ | 22 | 0 | 91 | (33) |
| Annual Hrs | 000'6 | 6,000 | 8,500 | 5,500 | 2,000 | 31,000 | | • | | 000'6 | 6,000 | 2,250 | 2,500 | • | 22,750 | (8,250) |
| FTEs | | | | | | 16.0 | | | | | | | | | 11.0 | (5.0) |
| | | | | | | | | | | | | | | | | |

COURT DEPUTIES

| Current Staffing | | | | | | | Proposed Staffing | Ing | | | | | | | ā | Difference |
|------------------|---------|---------|--------------|--------|---|--------|-------------------|---------|-----|--------------|-------|-------|--------|------|--------|------------|
| | 3rd - A | 3rd - B | 4th | Tunnel | ٦ | Total | 3rd - A | 3rd - B | 4th | S.E A | S.E B | S.E C | Tunnel | L.D. | Total | |
| 00.9 | - | | - | - | | 3 | | | | 1 | - | | - | | n | , |
| 2.00 | - | | - | - | | က | | | | - | - | | - | | e | • |
| 8.00 | . 0 | | 7 | - | | 20 | | | | - | - | 2 | - | | 2 | • |
| 00.6 | 1 74 | | 7 | - | | ις | | | | - | - | 2 | - | | S | • |
| 10.00 | - | | - | - | | e | | | | - | | | - | | ო | • |
| 11.00 | - | | ~ | - | | ო | | | | ۲. | - | | - | | ო | • |
| 12.00 | - | | - | - | | ო | | | | - - | - | | - | _ | ო | 1 |
| 13.00 | 7 | | 2 | - | | S | | | | - | - | 2 | - | | 2 | • |
| 14.00 | - | | - | - | • | က | | | | - | - | | - | | e | • |
| 15.00 | - | | - | - | | က | | | | - | - | | - | | က | |
| 16.00 | - | | - | - | | က | | | | - | - | | - | | ო | Î |
| 17.00 | - | | - | - | | က | | | | - | 1 | | - | | 3 | |
| Total Hrs | 15 | 0 | 15 | 12 | 0 | 42 | 0 | 0 | 0 | 12 | 12 | 9 | 12 | • | 42 | , |
| Annual Hrs | 3,750 | | 3,750 | 3,000 | • | 10,500 | • | | | 3,000 | 3,000 | 1,500 | 3,000 | | 10,500 | • |
| FTEs | | | | | | 5.0 | | | | | | | | | 5.0 | |

| urant Staffing | | | | Proposed Staffing | | | | Diffe | rence | | |
|--------------------|----------|------|-------------|--------------------|----------|------|------------|-------|--------------------|------|------------|
| British Street | FTE Cost | FTES | Total Cost | | FTE Cost | FTES | Total Cost | | | FTEs | Total Cost |
| Security Screeners | \$53,000 | 16 | \$848,000 | Security Screeners | \$53,000 | 11 | \$583,000 | Secu | Security Screeners | (2) | (265,000) |
| Jen Ities | \$67,000 | 5 | \$335,000 | Deputies | \$67,000 | 5 | \$335,000 | Deb | Deputies | | |
| Total Cost | | | \$1,183,000 | Total Cost | | | \$918,000 | Tota | otal Cost | | (265,000) |
| Toma coo. | | | | | | | | | | | |

King County Courthouse South Entrance Renovation Report

and the second of the second o

Attachment B: King County Department of Executive Services – Facilities Management Division

Courthouse South Entry Renovation Project

• Public Outreach Study

King County South Entry Renovation Outreach and Consultation with Key Stakeholders **Executive Summary**

Council Ordinance 15333, Section 114 required a study of the public use and the impacts to public access of both the reopened south entrance and the potential closure of the east and west entrances. The study was conducted in an outreach method to seek comment from principal user groups of the Courthouse. Stakeholders solicited for comment included those elected officials (other than the Council and Executive) where public functions are housed in the Courthouse, along with the department agencies located in the building.

Outreach Groups Presented and Asked for Comment

Superior Court District Court Prosecuting Attorneys Office King County Sheriff Office of Civil Rights Enforcement Department of Judicial Administration King County Bar Association King County Landmarks Commission Pioneer Square Preservation Board

Attached are the responses from each of these groups. The key issues raised in this outreach effort are summarized as follows:

City Hall Park

Reclaiming City Hall Park is important to the sense of security, and simply redesigning it will not change County employees' perception that traversing the park is unsafe. There is concern of the ability to renovate and patrol security issues after dark and on weekends. Money should spent, not in an effort to draw the general public to the space as a "park", but rather in creating the perception of the open space that is primarily reinforcing a "Grande Entrance" to the Courthouse. There is strong support for the idea of returning to the historic design of the entrance and lobby.

Security/Staffing/Stations

Reduction of security stations could result in long lines during busy periods; there will always be a need for more than two screening lines during peak times. Improved security may help change the negative perception now associated with the current City Hall Park, and the South Entry project should not be used as justification to reduce security staffing. Moreover, a new City of Seattle Command Center might generate more fire and police presence near the park.

Loading Dock/Deliveries

A new loading dock delivery system must include security for both ingress and egress. A security station above the tunnel might create a dual purpose of providing security for the building loading dock facilities as well as for the park. There is also concern that an underground loading dock may not be a feasible way to receive smaller deliveries.

3rd & 4th Avenue Closures

Emergency evacuation from the building must be considered (not feasible out of a single exit). There is concern about reasonable waiting time during peak periods if there are only two screening stations focused at the south entrance and one for the tunnel as a result of closing 3rd and 4th Avenues. Keeping them open would help keep those streets activated. Also, if 3rd and 4th Avenues are to be used for exit only, they should still be monitored by security in order to guard against improper entry.

South Entrance – King County Courthouse Summary of Stakeholder Comments

As a component of Facilities Management Division's, response to Council Ordinance 15333, Section 114, this paper represents a study of the public use, and the impacts to public access of both the reopened south entrance and the potential closure of the east and west entrances. The study was conducted in an outreach method to seek comment from principal user groups of the Courthouse. Stakeholders solicited for comment included those elected officials (other than the Council and Executive) whose public functions are housed in the Courthouse, along with the department agencies located in the building,

Outreach Groups Presented and Asked for Comment

Superior Court
District Court
Prosecuting Attorneys Office
King County Sheriff
Office of Civil Rights Enforcement

Department of Judicial Administration King County Bar Association King County Landmarks Board Pioneer Square Historic Board

Presentations to the stakeholders consisted of a short flash video demonstrating the original historic character of the Courthouse in the context of City Hall Park taken from photographs shortly after dedication in 1918, and interior photos of the original entrance with its marble finishes and stairways to the First Floor Lobby and the Second Floor.

Stakeholders were then shown the approximately 80% conceptual design developed as part of the Courthouse Seismic Project in December 2000, before it was eliminated from the project. Details of that design emphasized the overall character of a rehabilitated south entry recalling the original, and design concepts addressing modern requirements for building security, loading dock functions, and integration with City Hall Park. In support of integrating the park, City of Seattle's conceptual plan for City Hall Park, which was designed in 2006 to allow maximum flexibility for new King County south entrance, was also shown.

As a preface to the presentations, stakeholders were encouraged to comment on issues particularly relevant to each group's unique program requirements for use of the Courthouse, as well as general issues of functionality and security. They were also invited to consider the larger perspective of a public space defined by the Courthouse, City Hall Park, the surrounding building and sidewalks, and the space's use by County Employees, and the public.

Summary of Stakeholder Comments

The concept to provide a dignified entrance to Courthouse, to clean-up City Hall Park so that it can be a safe and secure public space for the public and employees was unanimously supported by all groups. Concern about the current condition of City Hall Park was a major concern, with

The concept of reconstituting a new south entrance to the Courthouse, designed with the intent of recalling the historic original entrance to the building, was unanimously supportive.

Judge Trickey, writing for Superior Court and the Judges:

- 1. Reclaiming City Hall Park important to the sense of security for those who would use the new South Entry.
- 2. South Entry project should not be used as justification to reduce security staffing. There will always be a need for more than two screening lines during peak times.
- 3. Restricting access to the ADA elevator to those with disabilities will be difficult. Two escalators would improve the flow, and reduce crowding around the security screening area.
- 4. There must be a comprehensive access plan for ADA that accounts for drop-off
- 5. New loading dock delivery system must include a security for both anything coming into the building, and going out.
- 6. Making 3rd and 4th Avenues exit only, will still requires security personel to guard against improper entry.

Other: Recommends a study of users who enter the building at various times of the day. Provide counts of strollers, luggage carriers, wheeled cases, hand trucks, etc. as well as those with disabilities.

Escalators: How much remodeling on the second floor will be necessary to accommodate the escalators.

Norm Maleng writing for the PAO

The public perception of City Hall Park is important to the success of a new South Entrance. Money should not be spent in an effort to draw the general public to the space as a "park", but rather the perception of the open space should be primarily that of reinforcing "Grande Entrance to the Courthouse. The function of a public open space to the formal entrance of an important public building is exemplified in the New York City's City Hall.

Security: Improved security may help change the negative perception now associated with the current City Hall Park.

Susan Rohr, Sheriff, writing for the Sheriff's Office:

Security: County Employees do not currently feel safe traversing the park in its current state, and simply redesigning it will not change this fact.

The number of security staff does not correlate with the number of entrances, or screening stations. With three stations at the South Entrance functioning at once, a single security assistant (Officer) is insufficient to observe the actions at all three stations.

Emergency evacuation from the building must be considered, and is not feasible out of a single exit. (South Side only)

Recognizing the historic precedence of the Courthouse, security requirements of the current time must also consider adequate space for security functions, including sight lines, and pull-aside inspections in the space.

If 3rd and 4th Avenues are to be used for Exit Only, they must also be monitored by security personnel because there is no way to guarantee unauthorized, or unscreened entry back into the building, compromising the whole system.

Deliveries: The number and types of deliveries to the building each day are many. The Sheriff's Office receives at least 10 deliveries of documents per day just from the outlying work sites. For heavier packages, the drop-off site must be a reasonable distance. The underground loading dock may not be a feasible way to receive smaller deliveries.

It is imperative that the Sheriff's Court Security Unit be actively involved in thee design process.

Bailey de longh, Office of Civil Rights

A passenger load/unload zone should be added as close to the building as possible to benefit all visitors, but especially those with disabilities. The existing such zone is along Fourth Avenue.

Provide that the ADA elevator will serve both Floors 1 and 2.

It is important to provide adequate space around the screening stations to allow an accessible route to the elevator and escalator(s).

Do not provide amenities such as a pergola, or other features that only benefit those using a non-accessible entry.

There is a significant concern about meeting the waiting periods should the number of screening stations be reduced.

Barbara Miner, Department of Judicial Administration

Concern for back-ups at the screening stations at peak times of day should the number of screening stations be reduced from three to two.

There could be a security impact to domestic violence victims as a result of having limited entrances and exits.

District Court staff also suggested that the 3rd and 4th Avenue entrances be used for exit only, and that the project consider designating a "staff entrance" to facilitate quicker entrance for King County employees.

King County Bar Association

A South Entrance would require walking additional distance for those approaching from the north in order to enter the building.

A reduction in the number of screening stations could increase wait times at peak period, which could in turn discourage jurors from serving, and make the Courthouse generally more inconvenient.

If the City of Seattle is unwilling or unable to renovate and patrol City Hall Park, there could be major security issues, especially after dark and on weekends.

King County Landmarks Commission

The Landmarks Commission supports the concept of returning the South Entrance to its status as main entrance, and has advocated this opinion since when the idea was studied in 2000 as part of the Courthouse Seismic project.

Pioneer Square Preservation Board

The Board expressed support of the concept of reopening the South Entrance and the thought that it would help the City Hall Park by creating a purpose for people to walk through the park, and keep eyes on the park.

King @Junty Courthouse New South Entrance Outreach Issues Matrix

pe The AKC of the PSHB question of the AKC of the PSHB question of the AKC of the PSHB question of the AKC of

ity for an escalator, citing that night be more flexible and nandle more people without the ms of maintenance.

10/31/2007

MICHAEL J. TRICKEY

PRESIDING JUDGE OF THE SUPERIOR COURT
KING COUNTY COURTHOUSE
516 THIRD AVE.
SEATTLE, WASHINGTON 98104

March 15, 2007

RECEIVED

MAR 19 2007

King County, CPD Facilities Management

Robert Renouard
Project Manager, LEED
Capital Planning and Development
Facilities Management Division
Department of Executive Services
500 Fourth Avenue, Room 320
Seattle, WA 98104-2337

RE: Restoration of South Entrance to King County Courthouse

Dear Mr. Renouard:

Thank you for this Monday's briefing on the status of the restoration project of the South entrance to the King County Courthouse. I appreciate being asked to submit a letter on behalf of the court summarizing its views on the project.

First, it is critical to emphasize that any effort to restore the original south entrance into the courthouse must include reclaiming City Hall Park. Many people, employees and citizens alike, feel unsafe walking through or near the Park. It will be difficult to convince people to use the south entrance if they continue to feel that the Park is dangerous.

Second, this project should not, and cannot, be justified as part of an effort to reduce security staffing. Closing other entrances does not mean there should be a reduction in the number of screening lines. There will always be a need for more than two security lines so that the public, including litigants and jurors, can easily enter the courthouse at peak times in the morning and after the lunch hour. We do not want long lines waiting to get into the courthouse during those times.

Third, unless you have a staff person "guard" the door, I envision difficulties restricting access to the new elevator to only those with disabilities. The pressure on the single escalator during the peak times in the morning and after lunch will lead folks to search out the elevator. Two escalators would be much better, and keep people flowing into the building rather than congregating around the security stations at the entrance.

Fourth, there must be a comprehensive plan for those with disabilities to enter the courthouse. With no ability to drive up and drop people off near an entrance, those with disabilities will struggle getting into the building.

Fifth, the elimination of the current loading dock will present challenges for all who make deliveries to the Courthouse. Any new delivery system must include a security component for screening everything coming into the building. Furthermore, the new loading dock must account for things going out of the building. We have judicial rotations yearly with judges and their furnishings moving between the three courthouses.

Sixth, it will be difficult to "close" the 3rd and 4th Avenue entrances and make them "exit only." People will surely try to gain entry to the building as others leave. There will need to be security staff at each entrance to insure that no one enters the building through the "exit."

Finally, has anyone done a study of those who enter on 3rd or 4th Avenue? Do we know the volume at various times of the day? Do we know how many people enter with strollers, luggage carriers, wheeled cases, or hand trucks? I am sure that some of these people as well as others without "disabilities" will need to use the elevator. Will one elevator be sufficient?

Sincerely

Judge Michael J.

Cc: Paul Sherfey Linda Ridge Norm Maleng Prosecuting Attorney W400 King County Courthouse . 516 Third Avenue Seattle, Washington 98104 (206) 296-9067 FAX (206) 296-9013

March 14, 2006

Robert Renouard Project Manager Facilities Management Division 500 Fourth Avenue, #320 Seattle, WA 98104

Dear Robert:

You had asked me for a letter summarizing my comments from our meeting where we discussed the South Entry Project and "City Hall Park". As I shared with you during our meeting, I urge those working on this project to give some thought to what they mean by the term "park". To many, the word "park" conjures up a specific use and image, and most people believe that parks are used by members of the general public.

With regard to the new proposed "City Hall Park", this is not an area that will likely be used by the general public as a park, in the traditional sense of the word. It is more likely that the area South of the Courthouse will be used as open space in conjunction to any new, grand entry to the building.

I would caution anyone working on this project against believing that simply designating the area South of the Courthouse as a park and spending money to spruce up the area will automatically draw members of the public to use it for such. This area is unlikely to draw many who work North of the Courthouse. It may not become the attraction that the project is hoping for.

This area may be better served as part of the "grand entrance" to the Courthouse. If that were the theme of the design for this area, it may reinforce its function as such. Many people who use the Courthouse will pass through this area (assuming that the grand entrance is completed). It should be pleasant, inviting, and functional. In other words, the project could define the users of this proposed "park" area if they were to redefine the "park" as part of the "grand entrance".

If the project considers this approach, it may want to study analogous public buildings that have grandentry style parks or open space. An example that comes readily to mind is New York City Hall.

My final comment is about security. The project may want to examine what would be the appropriate level of security for this area. Improved security may help change people's perception of this area, and may increase the number of individuals who pass through this area.

Please do not hesitate to contact me if you have any questions regarding my comments or if you would like to discuss this topic further.

Sincerely,

NORM MALENG
Prosecuting Attorney



KING COUNTY SHERIFF'S OFFICE 516 Third Avenue, W-116 Seattle, WA 98104-2312 Tel: 206-296-4155 • Fax: 206-296-0168

Susan L. Rahr Sheriff

April 2, 2007

Robert Renouard Project Manager Facilities Management Division 500 Fourth Ave. #320 Seattle, WA 98104

Dear Robert,

You asked me to summarize my comments from our meeting about the "South Entry" project and City Hall Park. Rather than repeating Prosecutor Norm Maleng's and Judge Michael Trickey's comments about the park, I will simply state that I agree with them and add that the employees of the courthouse do not feel safe traversing the park in its current state to enter the courthouse. Simply redesigning the area as a "park" will not change that fact.

With regard to the proposed new south entrance, I will summarize the issues I raised to you in our meeting.

First, and foremost, this new entrance may not reduce the security staffing needs of the courthouse. It is an erroneous assumption that the number of entrances is directly correlated to the number of security staff necessary to safely move people into and out of the courthouse. As we discussed, the more appropriate correlation is the number of people entering and exiting the courthouse. We will need a sufficient number of screening stations to get people into the courthouse in a reasonable amount of time. We already experience backups during the morning rush and lunch hour with two external entrances. If we reduce that to one entrance, we will need to have at least three screening stations at that entrance. For proper operations, each screening station requires three screeners. And with three stations going at once, it is not possible for a single Security Assistant to properly monitor and address safety issues. We must also consider emergency evacuation of the building. It is simply not feasible to accomplish this through a single exit.

I also shared with you my concern that the new south entrance be designed with security in mind. I fully appreciate the wish to respect the history of the building. However, in 2007 we must be mindful of greater security risks as well. The south entrance will need

to be of sufficient size to accommodate three screening stations and allow appropriate line of sight for the security assistants to effectively monitor the activities and have an area to take people aside for additional screening when necessary.

We also discussed whether the current 3rd and 4th Avenue entrances might be used for "exit only" or for employees. If these entrances are not monitored by security personnel, there is no way to guarantee that people exiting will not inadvertently (or deliberately) allow unauthorized, unscreened access to the building. To do so compromises the entire system.

Another issue that must be addressed is the many, many small deliveries that are made to the courthouse each day. These include carts of documents and other items from King County departments outside the building. For example, the Sheriff's Office alone has over ten deliveries a day of documents, packages of evidence, and other items brought to and from the courthouse just from our outlying work sites. This does not include many deliveries from Fed Ex, UPS, etc. There needs to be parking within a reasonable distance to transport these heavy items. (I don't believe the new underground loading dock is a feasible way to address these smaller deliveries.)

We also discussed the new loading dock concept. Because the design is much less clear I can only comment that there must be a screening process for deliveries, as we have currently. The number of security personnel will depend on the design.

This list of concerns is not exhaustive. As we discussed, it is imperative that a representative from my Court Security Unit be actively involved in the design process for the new entrance and other building entrances. Thoughtful design can certainly reduce the risks, as well as perhaps reduce the number of personnel necessary to ensure the safety of the building. But this will need to be a collaborative process from the start.

I am very willing to assist in any way I can to make the new south entrance project successful. Please do not hesitate to contact me.

Sincerely.

Sue Rahr

King County Sheriff



Office of Civil Rights

Department of Executive Services

400 Yesler Way, Room 260 Seattle, WA 98104-2683 **206.296.7592** TTY 206.296.7596 www.metrokc.gov/dias/ocre

DATE:

April 4, 2007

TO:

Robert Renouard

FROM:

Bailey de longh, Director

Karen Ozmun, Disability Compliance Specialist

SUBJECT:

Courthouse South Entry Project

Thank you for meeting with us on March 14, 2007, regarding this project. We appreciate the opportunity to comment on the existing drawings, and outline some general concerns to be addressed in developing designs.

Overview

We strongly encourage a design that maximizes integration of people with and without disabilities, including integration of the accessible route with other routes into and through the courthouse. Where routes may not be integrated due to structural or grading constraints, we strongly support design that will provide equal access.

Feature

Recommendations and Comments

Drop off/pick up

Strongly recommend adding a passenger load/unload zone, which will benefit all visitors to the courthouse, but particularly individuals with disabilities. We recommend that the zone be located as close to the entrance as possible, as people who need to use the passenger load/unload zone often have difficulty navigating distances. The existing passenger load/unload zone is right in front of the 4th Avenue entrance/exit.

Power doors

Strongly recommend installing at least one power door. It is an effective way to ensure compliance when achieving and maintaining door opening force maximum lbs. has historically been a challenge in compliance. Also, even if opening force requirements are met, there are people with disabilities that have difficulty with manual doors due to issues of range of motion, balance, strength and dexterity.



Power doors help ensure equal access to all members of a diverse community, and reflects current best practices in building design. Power doors have been installed at the existing 3rd Avenue entrance, Regional Justice Center, King Street Center, and soon-to-open New County Office Building. (Also, Seattle Justice Center, Seattle City Hall, and Seattle Public Library.)

In addition, power doors are of benefit to individuals with strollers, attorneys with carts carrying trial materials, and delivery services.

Power door switch Strongly recommend using a bollard style switch which may be activated at both the maximum height of 36" and at foot pedal height for wheelchair users. Such a switch will be installed at the New County Office Building. Some people with disabilities do not have range of motion or strength to activate standard power door switches, and this switch provides an option to activate with a wheelchair foot pedal.

Potential switch

Wikk Industries - Ingress'r Tall Switch (planned for NCOB) http://www.wikk.com/sw_spec.html

Screening stations Because the south entrance project is an alteration, new construction requirements apply. In our view, all screening stations should meet accessibility requirements, including clear width for magnetometers. Having all screening stations accessible ensures efficient passage for all individuals and integrates people with and without disabilities.

Benches

Reference: Plan A3.2 dated 12-28-00, F-G/10 and H-K/10 There are two benches located below wall art. Per code, in our view, we need to provide a wheelchair space in line with these benches, to ensure equal access to sit, alone or next to a friend or colleague, and not be stuck in space intended for pedestrian traffic. [See ICC/ANSI A117.1-2003 903]

Elevator/escalator

Reference: Plan A3.2 dated 12-28-00, E/10 Provide an elevator that will serve both floors 1 and 2. Per consultation with U.S. Department of Justice, if technically feasible, we should provide an accessible route to both floors from the entry level, as is provided in non-accessible routes by stairs to floor 1 and by escalator to floor 2.

Escalator access

Reference: Plan A3.2 dated 12-28-00, E/10 There appears to be insufficient room between the screening station and access to the escalator. This could result in

Renouard, FMD-CIP, 4-4-07 Page 3 of 3

restricted movement of visitors at security and/or trying to get

to/from the escalator.

No revolving door

We strongly support the decision not to use a revolving door at any of the entries to the courthouse, due to accessibility issues.

No pergola

Reference: Plan A3.2 dated 12-28-00

We support the decision not to retain a pergola that provided weather protection only to those who are able to use a non-

accessible entrance.

Screening stations Reference: Plan A3.2 dated 12-28-00

We have significant concern about the planned reduction of total screening stations at entries to the courthouse. Setting aside the Administration Building/tunnel screening station, three major screening stations will be reduced to two. With incoming traffic being focused at one entrance, will two screening stations be functionally adequate and achieve reasonable wait time for

visitors when it is busy?



Department of Judicial Administration Barbara Miner Director and Superior Court Clerk (206) 296-9300 (206) 296-0100 TTY/TDD RECEIVED

APR 09 2007

Fing County, CPD

April 4, 2007

Robert Renouard, Project Manager Capital Planning and Development Section Facilities Management Division, DES ADM-ES-0320

RE: Courthouse South Entrance Comments

Dear Robert:

Thank you for presenting the South Entrance project information to me. Your presentation was very informative and the project is interesting.

I have shared the information with the staff and management team within the Department of Judicial Administration. Though there was strong support the idea of returning to the historic design of the entrance and lobby areas, there were strong concerns expressed about the implications of the project. Those concerns include:

- The bottleneck that would develop at the security line entrances at peak times of the day due to the reduction in the number of entrance paths. This concern with this issue cannot be stressed enough; the impact is estimated to be very high;
- The potential changes to the loading area and the affect of those changes on departmental operations; and
- The potential security impact of having limited entrances/exits for domestic violence victims. The limited options increase the possibility of contact leading to issues between petitioners and respondents/defendants and victims.

Several suggestions were also offered:

- A suggestion to use the 3rd/4th avenue doors as at exit doors; and
- A suggestion to make a staff entrance to facilitate quicker entrance for the county employees.

Thank you for the opportunity to provide feedback. Please contact me should you have any questions.

Sincerely,

Barbara Miner

Director and Superior Court Clerk



1200 Fifth Avenue, Suite 600 Seattle, WA 98101

> 206.267.7100 206.267.7099 fax

APR 16 2007

www.kcba.org

April 13, 2007

Mr. Robert Renouard
Capital Project Manager for Capital
Planning and Development
King County Department of Executive Services
500 Fourth Avenue
Suite 320
Seattle, WA 98104

Proposal to Reopen South Entrance of King County Courthouse

Dear Robert:

Re:

Thank you for your recent presentation to the King County Bar Association Bench-Bar Liaison Committee regarding the proposal to reopen the south entrance of the King County Courthouse.

I was unable to put the proposal before the King County Bar Association Board of Trustees for full consideration at its most recent meeting because of previously scheduled matters that had to be addressed.

I have discussed the proposal informally with members of the Board. They have expressed interest in the plan, insofar as it would restore and showcase the architectural beauty of the original main entrance. Several members expressed concern, however, that the proposal might draw objections from lawyers and from the public for the following reasons:

- 1. Persons approaching the courthouse from the north would have to walk an additional distance to get to the south side of the courthouse in order to enter the building.
- 2. If the number of security stations were to be reduced, there could be long lines to get into the courthouse during busy periods, which, in turn, could discourage jurors from serving and which could make the courthouse generally more inconvenient to use.
- 3. If the City of Seattle is unwilling or unable to renovate and patrol the city park adjacent to the south entrance, there could be major security issues, especially after dark and on weekends.

OFFICERS John R. Ruhl President

Eileen M. Concannon First Vice-President

Daniel Gandara Second Vice-President

Anne M. Daly Secretary

James A. Andrus Treasurer

TRUSTEES

Amelia J. Adair '07

Bonnie J. Glenn '07

Karen W. Murray '07

Jeffrey M. Sakoi '07

Carl E. Forsberg '08

Mark J. Hillman '08

Andrew W. Maron '08

Loretta Sue Story '08

J. Mark Weiss '08

Carllene M. Placide '09

Terence J. Scanlan '09

ABA DELEGATE Peter S. Ehrlichman

CHAIRPERSON YOUNG LAWYERS DIVISION Derek D. Crick

EXECUTIVE DIRECTOR
Alice C. Paine

Mr. Robert Renouard King County Department of Executive Services April 13, 2007 Page 2

If you wish, I can put this matter on the KCBA Board's agenda for a future meeting, and you can make a full presentation to the Board. In the meantime, I hope that this information is helpful to you in your planning process.

Sincerely,

John R. Ruhl

JRR:cls

cc: Alice C. Paine, KCBA Executive Director

Hon. Michael Trickey

08552299.doc

King County Landmarks Commission Design Review Committee- Minutes April 12, 2007

draft

COMMITTEE BRIEFING

King County Courthouse South Entry Rehab, Seattle, WA Robert Renouard, King County Facilities Management

Tonie Cook presented information on the proposed 2000 Courthouse Seismic and Additive Alternative Plan that includes rehabilitating the south entrance to the building. She said the portion of the south entrance plan was deferred due to budget and other considerations. She noted two items in the packet: a March 2000 letter, signed by Landmarks Commission Chair Patrick Schneider, and copies of section of a 17-page Executive Summary of the six-volume Facility Program Plan prepared in association with the H3 Facility Project. (See Attachments 1 and 2, dated March and September 2000.) The documents address the south entry and park rehabilitation issues. The Schneider letter articulates the Landmarks Commission's support for the project. Julie Koler said the 1988 Cardwell Study was the initial document that set the stage for on-going discussions about south entrance rehabilitation. She said that over time, however, the plans have changed. Robert Renouard said that the 2000 report represented only 80 percent design and, since that time, changing functions/needs have necessitated revisions to the plan.

Renouard asked the Committee for a letter of support for the project, including members' thoughts on design direction and any other issues of concern. Committee members expressed concern that they are not sufficiently familiar with the project to provide any detailed comments. Renouard then presented current plans for City Hall Park including a new traffic area for vehicle deliveries and pedestrians, elimination of the tunnel and most parking; and then gave an overview of interior elements of the lobby including security stations and escalator. He passed around a water color wash of the proposed south entry. The Committee noted that it contains elements reminiscent of the original 1916 entrance.

The Committee discussed the Cardwell Study; its recommendation to return the south entrance to its original status as main entrance; the current security and operational requirements; the period of significance; determining the new design's compatibility with the historic exterior that does not restore or reconstruct the original exterior; and how to support the current project without adequate review by the full Landmarks Commission. Committee members noted that, unless there have been significant changes to the 2000 schematic plan, there is no reason to think the Commission will not continue its stated support for the direction of the project.

Chair Rich said that a letter from the Commission would be more appropriate than from the DRC and recommended a presentation at the April 26, 2007 meeting, including an overview of the Courthouse. He asked that copies of the Cardwell Study be distributed to commissioners. Tonie Cook offered to provide a copy of the meeting notes to Robert Renouard for use in moving towards a current support letter similar to the 2000 letter from the Landmarks Commission Chair.



The City of Seattle

Pioneer Square Preservation Board

Mailing Address: PO Box 94649 Seattle WA 98124-4649 Street Address: 700 δth Ave Suite 1700

PSB 89/07

Daniel Mitchell

ARCHITECTURAL REVIEW COMMITTEE REPORT

From 4/1//07 ARC Meeting for 4/18/07 Board Meeting

Committee Members Present: David Strauss, Sonja Sokol Furesz, Adam Hasson, Lorne McConachie

Board Members Please Note: The citations from the District Ordinance, Rules for the Pioneer Square Preservation District, and Secretary of the Interior's Standards listed below are for your consideration in addition to any other citations you find relevant in considering each application.

APPLICATIONS FOR CERTIFICATES OF APPROVAL

041107.11

Trattoria Mitchelli

Travelers Hotel building

84 Yesler Way

Summary of Application:

Signage: Apply business signage to the inside of the windows in black, red and

yellow.

ARC Report:

ARC members reviewed the sign renderings, photos and color samples. Mr. Hasson asked if the light fixtures existed or proposed new. Mr. Mitchell, business owner, said they were existing. Mr. Mitchell clarified for the ARC that although the east façade rendering did not show the windows that they would be applied at the same height as shown in the rendering for the Yesler façade. ARC acknowledged that the M, which is a graphic fork design was larger than 10 inches but ARC members thought it could be allowed as part of reduced sign package per the district rules. ARC also thought that it was more like a logo than a letter and the size was okay. ARC recommends approval of the application.

Staff Report: No staff report

Draft Motion: I move to approve a Certificate of Approval for the project as presented

per:

Code Citations:

District Rules XX. Rules for Transparency, Signs, Awnings and Canopies

A. Transparency Regulations

C.1. Letter size

SMC 23.66.160 Signs

Administered by The Historic Preservation Program
The Seattle Department of Neighborhoods
"Printed on Recycled Paper"

041107.12 The Nord Building

Alisha Langston Bond

312 1st Ave

Summary of Application:

Remove and replace existing telephone intercom system.

ARC Report: ARC reviewed the photos, and spec sheets provided. ARC members asked for clarification of the how the installation will affect the brick. Ms. Langston Bond, Pioneer Construction Management, said that the new panel is face mounted so they do not plan to remove any brick. She said they thought that there is existing brick behind the old panel above which would be revealed by the new shorter panel. She said that if they find that the brick is damaged they will replace it in-kind. ARC asked that they specify that in their application. ARC will recommend approval of the application.

Staff Report: Pioneer Construction Management provided confirmation in writing that they will, if necessary, replace any damaged brick in kind.

Draft Motion: I move to approve a Certificate of Approval for the project as presented per:

Code Citations:

District Rules III General Guidelines for rehabilitation and new construction SMC 23.66.180 Exterior Design

Secretary of Interior Standards for Rehabilitation 1,2,3,5

041107.13 Main Street Gyros

Tareq Alzer

301 2nd Ave Ext S

Summary of Application:

Street Use: Install a sidewalk café with 2 tables on the Main St. side of the building and 2 tables on the 2nd Ave Ext S side of the building.

ARC Report: ARC reviewed the layout, and photos of table and chairs and building as exists. The placement as well as the chairs and tables were found to meet rules. Staff reminded applicant that SDOT also has to approve the tables and chairs on the side walk so they will need to make application with them as well.

Staff Report:

Draft Motion: I move to approve a Certificate of Approval for the project as presented ner:

Code Citations:

District Rules XIII Sidewalk cafes

PRELIMINARY PROJECT REVIEW

041107.2 King County Courthouse

Robert Renouard

Briefing on possible re-establishment of the south entrance.

ARC Report: Mr. Renouard, Project Manager, King County, FMD gave a briefing on the possibility of re-establishing the south entrance to the King County Courthouse. Mr. Renouard explained that the King County Council had required outreach for the potential project so he is meeting with stakeholders to get initial feedback. The King County Landmarks Board will be reviewing the project. Mr. Renouard showed old pictures of the interior of the lobby and explained that some pieces such as the curved

Dr. O. M. June

stairs had been removed. He explained that they found some stairs under the loading dock. Mr. Renouard showed a set of conceptual plans and explained how the new entrance would function. He explained that the other entrances at 3rd and 4th may be converted to exit only or emergency exits with the security being centralized at the south entrance. Mr. Renouard said they would likely not install the revolving door shown in the plans. ARC members commented that King County may want to study if the escalator is necessary or if the building could be better served by stairs, which may handle more people, be more flexible and breakdown less.

Mr. Renouard explained that the pattern shown on the exterior courtyard is a placeholder still to be determined. Mr. Renouard explained some of the issues that need to be resolved as part of the re-opening of the south entrance. There is mechanical equipment in the court yard. He said they have been able to relocate some of the equipment to other locations while others new location still needs to be determined. In order to re-open the south entrance, the loading dock functions would need to be moved. Mr. Renouard showed ARC a layout of the park and showed the tunnel that accessed the building. He acknowledged that the walls to the tunnel are historic. A security station would need to be at the entrance to the tunnel at the south end of the park but far back enough to not block traffic. Mr. Renouard explained that a shear wall was applied as seismic upgrade but that is now in the way of using one of the lanes. Resolutions they are exploring include making it a controlled one lane tunnel, having some kind of shuttling system or a cut and cover to widen the tunnel. The cut and cover may include a turn around and possible minimal parking. Mr. Renouard said that more parking may be too costly. If the City Hall Park plan is implemented which would convert Dilling Way to a pedestrian path, they would have an additional issue of finding a new location for ADA parking. Attorneys also expressed the desire to have close parking.

ARC members expressed support of the concept of reopening the south entrance and thought that it would help the park by creating a purpose for people to walk through the park and keeping eyes on the park. ARC also expressed that the entrance should be integrated with the park.

Mr. Strauss expressed that he though keeping the 3rd and 4th Street entrances open would help keep those streets activated. He also thought that if the security station could be located above the tunnel it might create a dual purpose of also providing eyes on the park.

Mr. Hasson pointed out that the new Command Center down the street would create more fire and police traffic by the park. Mr. Hasson expressed that he would like to see what the alternatives were and then could look at it in terms of how it affects historic features and how the historic features could be lease affected.

Mr. McConachie said he would also like to see more details of the alternatives. He would like more information about what exists that is historic, what has been changed and how that evolved. He said with that understanding they could evaluate if it was okay if it was partially restored, better than what is now, but at least the entrance is open. ARC member mentioned they would like to know more about the current conditions, if there are other original features, particularly on the exterior that exist but are hidden or are there missing architectural features. Mr. Renouard will return to ARC once the alternative plans have further developed.

Issued:

May 16, 2007

Genna Nashem

King County Courthouse South Entrance Renovation Report

Attachment C: King County Department of Executive Services – Facilities Management Division

Courthouse South Entry Renovation Project

en de la figure de la filono de la persona frage de la persona de la composition de la filono de la filono de La cambionidad de la filono de l

• Life Cycle Costs Analysis

\$12.94 63.4% 6%

| | | Option 1 | Option 2 | Option 3 | Option 4 |
|----------|---|---|------------------------------------|--------------------------|---------------------|
| | | Deputies at 3rd / 4th | | No Deputies at 3rd / 4th | No Deputies at 3rd/ |
| | | Ave | Deputies at 3rd / 4th Ave | Aven | 4th Ave |
| | | 4 Hr. Loading Dock | No Loading Dock | 4 Hr. Loading Dock | No Loading Dock |
| | 3rd and 4th avenue exit staffing | yes | yes | ou | ou |
| | 3rd and 4th Avenue Security Doors | ou | 00 | Ves | Ves |
| | Loading Dock | 4 | 0 | 4 | 0 |
| | Loading Dock Included | yes | ou | yes | ou |
| Comments | Option 3 might have capital impacts on the new KC Admin CIP | on the new KC Admin C | IP | | |
| | Capital Cost | \$16,500,000 | \$8,500,000 | \$16,800,000 | \$8,900,000 |
| | Historic Preservation Grant | (\$800,000) | (\$800,000) | (\$800,000) | |
| | Annual Staffing Cost | \$123,000 | \$3,000 | (\$212,000) | |
| | LCC Capital | \$10,700,000 | \$5,300,000 | \$10,900,000 | \$5,600,000 |
| | LCC Staffing | \$1,600,000 | 80 | (\$2,700,000) | _ |
| | Total LCC | \$12,300,000 | \$5,300,000 | \$8,200,000 | \$2,200,000 |
| Notes: | | | | | |
| | Capital cost assumes 25 year financing at 5% with 6% interim financing and transaction costs LCC Capital includes replacement of elevator and escalators. | ing at 5% with 6% inter felevator and escalator: | im financing and transaction :. | ı costs | |
| | Staffing costs assume 3% annual inflation on salaries Analysis period is 40 years and use of a 7% real discount rate | ation on salaries of a 7% real discount rai | u | | |

LCC Factor for staffing
LCC factor for capital
Add on factor for construction financing and transactions

King County Courthouse South Entrance Renovation Report

Attachment D: The Robinson Company

Courthouse South Entry Renovation Project

- Conceptual Design Estimate Summary and
- CIP Project Cost Estimate Summaries



| | | | King County Mods | <u>s</u> | |
|---|---------------|-----------------------------|---|---|---|
| | | | LCC Opt. 1 | LCC Opt. 2 | LCC Opt. 3 |
| SOUTH ENTRY INTERIOR RENOVATION | ⇔ | 3,620,976 | \$ 3,620,976 | \$ 3,620,976 | \$ 3,620,976 |
| PEDESTRIAN PLAZA/EXTERIOR WORK | \$ | 1,015,963 | \$ 1,015,963 | \$ 1,015,963 | \$ 1,015,963 |
| RAMP/LOADING DOCK & TUNNEL | ⊗ | 4,972,712 | \$ 4,972,712 | \$ 4,972,712 | 0 |
| GENERAL CONDITIONS | 99 | 922,527 | \$ 922,527 | \$ 922,527 | \$ 445,146 |
| SUB-TOTAL | 8 | 10,532,178 | \$ 10,532,178 | \$ 10,532,178 | \$ 5,082,085 |
| ALTERNATES: 1 Revolving door exits @ 3RD & 4TH streets 2 Additional stop @ new ADA elevator 3 Granite pavers @ 100% of plaza | ∞ | 251,789 62,460 77,274 | (b) \$ 377,684 (a) \$ \$ 62,460 \$ \$ \$ 77,274 | s) \$ 125,895 (b) \$ \$ 62,460 \$ \$ \$ 77,274 \$ | \$ 377,684 3rd door added per Sheriff meeting 11/1/07 \$ 62,460 \$ 77,274 Requirement of Historic Grant |
| TOTAL MACC | | | \$ 11,049,596 | \$ 10,797,807 | \$ 5,599,503 |
| | | | | | |

| Š: | |
|----|--|
| Õ | |
| 5 | |
| X | |
| Ш | |

STATE SALES TAX
TESTING AND INSPECTIONS
CONSTRUCTION CONTINGENCY
ARCHITECT/ENGINEERING FEES
PERMITS
ASBESTOS REMOVAL

PARK REDEVELOPMENT/LANDSCAPING CANOPY @ PLAZA SECURITY EQUIPMENT REPROGRAMMING 3RD AVE ENTRANCE TOXIC SOILS/MATERIALS REMOVAL

| Third revolving door at So. Lobby Exit | 2-door estimate | 3rd door | Total 3 Doors | |
|--|-----------------|----------|---------------|--|
| revolving door | 251,789 | 125,895 | 377,684 | |
| Third | جو | (a) | \$ (9) | |

| GENERAL CON | CONDITIONS CALCS | 69 64 | 3,620,976 | so se | 3,620,976 | <i>د</i> ه ده | 3,620,976 |
|-------------|------------------|--------------|-----------|-------|-----------|---------------|-----------|
| ₩. | 922,527 | · • | 4,972,712 | • | 4,972,712 | | |
| · 69 | 9,609,651 | S | 9,609,651 | S | 9,609,651 | € | 4,636,939 |
| | %09.6 | | %09.6 | | %09.6 | | %09.6 |
| | | S | 922,527 | S | 922,527 | S | 445,146 |



PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION - SOUTH ENTRY/LOBBY

LOCATION: SEATTLE, WA

BLDG SF:

ESTIMATE: 2007096

EST TYPE: COST MODEL

| DIVISION | DESCRIPTION | | TOTAL | \$/SF |
|----------|---------------------------------------|--------|-----------|-------|
| A10 | FOUNDATIONS | | 7,500 | |
| B10 | SUPERSTRUCTURE | | 119,310 | |
| B20 | EXTERIOR CLOSURE | | 270,000 | |
| C10 | INTERIOR CONSTRUCTION | | 293,602 | |
| C30 | INTERIOR FINISHES | | 802,208 | |
| D10 | CONVEYING SYSTEMS | | 498,000 | |
| D20 | PLUMBING | | 45,945 | |
| D30 | HVAC | | 117,453 | |
| D40 | FIRE PROTECTION | | 34,155 | |
| D50 | FLECTRICAL | | 280,906 | |
| F20 | SELECTIVE BUILDING DEMOLITION | | 119,500 | |
| 120 | ESTIMATE SUBTOTAL | | 2,588,579 | |
| | DESIGN CONTINGENCY @ | 12.00% | 310,629 | |
| | SUBTOTAL | | 2,899,208 | |
| | GENERAL CONTRACTOR'S OH & P @ | 8.00% | 231,937 | |
| | SUBTOTAL | | 3,131,145 | |
| | ESCALATION TO 06-JAN-09 (10.00%/YR) @ | 15.64% | 489,831 | |
| | TOTAL | | 3,620,976 | |

EXCLUSIONS:

SEE ESTIMATE SUMMARY

PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION - SOUTH ENTRY/LOBBY

2007-0618

LOCATION: SEATTLE, WA

BLDG SF:

ESTIMATE: 2007096

EST TYPE: COST MODEL

| ITEM | DESCRIPTION | | QUANTITY UNIT | UNIT COST | TOTAL | \$/SF |
|-------|------------------------------|------------------------|---------------|-----------------|---------|-------|
| A10 | FOUNDATIONS | | | | | |
| 03300 | ELEVATOR PIT-ADA | | 1 EA | 7,500 | 7,500 | |
| A10 | FOUNDATIONS | | DIV | ISION TOTAL | 7,500 | |
| | | | | | | |
| B10 | SUPERSTRUCTURE | | | 0.500 | 2,500 | |
| 03380 | ADA ELEV HOIST BEAM | | 1 LS | 2,500 | 22,000 | |
| 03380 | CIP BEAMS @ ESCALATOR | | 1 LS | 22,000 | 22,000 | |
| | | LEVEL 1A & 2 | 470.05 | 75.00 | 13,200 | |
| 03380 | CIP STAIRS TO ELEV LOBBY | | 176 SF | 75.00 | 31,680 | |
| 03380 | ELEVATOR RAISED PIT/SLAB | | 176 SF | 180 | 31,000 | |
| | | LEVEL 2 | | 45.00 | 45 400 | |
| 03380 | FLOOR STRUCT @ ESCALATOR | | 336 SF | 45.00 | 15,120 | |
| | | LEVEL 1A | | | 44.040 | |
| 03380 | FLOOR STRUCT TO ADA ELEV. | | 318 SF | 45.00 | 14,310 | |
| | | LEVEL 1 | | | | |
| 05510 | BRONZE HANDRAILS | | 46 LF | 200 | 9,200 | |
| 05600 | BRONZE CLADDING @ ELEV. DOOR | | 1 LS | 1,300 | 1,300 | |
| | · · | RELOCATE EXISTING | | | | |
| 06110 | MISC ROUGH CARPENTRY | | 1 LS_ | 10,000 | 10,000 | |
| B10 | SUPERSTRUCTURE | | DIV | ISION TOTAL | 119,310 | |
| B20 | EXTERIOR CLOSURE | | | | | |
| | EXT. BRONZE ENTRY DOORS-PR | | 3 EA | 90,000 | 270,000 | |
| 08110 | EXT. BRONZE ENTRY DOORS-FR | BALANCED | | 00,200 | • | |
| D20 | EXTERIOR CLOSURE | DALANOLD | | ISION TOTAL | 270,000 | |
| B20 | EXTERIOR CLOSURE | | 5.1 | ,,0,0,1,10,1,12 | 2.0,555 | |
| C10 | INTERIOR CONSTRUCTION | | | | | |
| 04220 | ELEVATOR CORRIDOR WALLS | | 756 SF | 22.00 | 16,632 | |
| 04220 | ELEVATOR MACHINE ROOM WALL | | 275 SF | 22.00 | 6,050 | |
| 04220 | ELEVATOR SHAFT WALL | | 1,242 SF | 22.00 | 27,324 | |
| 04220 | WALLS @ ESCALATOR | | 1,770 SF | 22.00 | 38,940 | |
| 08110 | NEW INT DOOR @ BASEMENT | | 3 EA | 1,800 | 5,400 | |
| 08350 | NEW INT DOORS/GLAZING | | 1 LS | 20,000 | 20,000 | |
| | (0 | 2) 2ND FLOOR ESCALATOR | | | | |
| 08810 | GLAZING @ EXIT VESTIBULE | | 173 SF | 80.00 | 13,840 | |
| 09110 | MTL STUD ARCHED SOFFITS | | 1,064 SF | 28.00 | 29,792 | |
| 09110 | MTL STUD FLAT SOFFITS | | 412 SF | 18.00 | 7,416 | |
| 09110 | MTL STUD FRAME/GWB COLUMNS | | 2,628 SF | 16.00 | 42,048 | |
| 09110 | MTL STUD FURR/GWB WALLS | | 4,320 SF | 13.00 | 56,160 | |
| 10000 | MISC SPECIALTIES | | . 1 LS | 30,000 | 30,000 | |
| | | | DI | VISION TOTAL | 293,602 | |
| C10 | INTERIOR CONSTRUCTION | | | | | |
| | INTERIOR CONSTRUCTION | | - | | | |

| ITEM | DESCRIPTION | QUANTITY UNIT | UNIT COST 20 | 00797648 | \$/SF |
|----------------|--|---------------|-------------------|------------------|-------|
| | | 410 | 3E 000 | 35,000 | |
| 06200 | MISC FINISH CPTRY/TRIM | 1 LS | 35,000 5,000 | 5,000 5,000 | |
| 06200 | RELOCATE SECURITY STATIONS | 1 LS | 5,000 | 3,000 | |
| | SCREENWALI | 1 LS | 6,500 | 6,500 | |
| 06220 | EXIT VESTIBULE TRIM | 1 LS | 135,000 | 135,000 | |
| 06250 | GFRG MOULDING/TRIM INSTALLE | | 100,000 | | |
| 09220 | PREMIUM-VENEER PLASTER | 8,424 SF | 12.00 | 101,088 | |
| 09220 | EXT STONE CLADDING ALLOWANCE | 1 LS | 35,000 | 35,000 | |
| 09310 | MARBLE CLADDING ALLOWANCE | 1 LS | 362,000 | 362,000 | |
| 09380 | ALLOW FOR NEW @ STAIRS | 252 SF | 60.00 | 15,120 | |
| 09380 | ALLOW REPLACE DAMAGED | 500 SF | 35.00 | 17,500 | |
| 00000 | ASSUME 25 | 5% | | | |
| 09380 | RENOVATE EXST'G MARBLE FLOORING | 2,000 SF | 15.00 | 30,000 | |
| 09900 | ALLOW FOR PROTECTION/RELOCATION OF ARTWORK | 1 LS | 10,000 | 10,000 | |
| 09900 | INTERIOR PAINTING ALLOWANCE | 1 LS | 15,000 | 15,000 | |
| 09900 | MISC INT FINISHES | 1 LS | 35,000 | 35,000 | |
| C30 | INTERIOR FINISHES | DIV | ISION TOTAL | 802,208 | |
| | | | | | |
| D10 | CONVEYING SYSTEMS | | 100 000 | 400,000 | |
| 14210 | ELEVATOR REWORK @ LOBBY | 1 LS | 160,000 | 160,000 | |
| 14240 | ADA ELEVATOR/2-STOP/2 DOOR | 1 EA | 68,000 | 68,000 | |
| 14410 | ESCALATOR | 2 EA | 135,000 | 270,000 | |
| D10 | CONVEYING SYSTEMS | DI\ | ISION TOTAL | 498,000 | |
| | | | | | |
| D20 | PLUMBING | 410 | 45.045 | 45,945 | |
| 15400 | PLUMBING | 1 LS | 45,945 | 45,945 45,945 | |
| D20 | PLUMBING | ווט | ISION TOTAL | 45,545 | |
| | 1944 | | | | |
| D30 | HVAC | 410 | 447.452 | 117,453 | |
| 15700 | HVAC | 1 LS | 117,453 | | |
| D30 | HVAC | יוט | VISION TOTAL | 117,453 | |
| _ :_ | | | | | |
| D40 | FIRE PROTECTION | 1 LS | 34,155 | 34,155 | |
| 15300 | FIRE PROTECTION | | | | - |
| D40 | FIRE PROTECTION | יוט | VISION TOTAL | 34,155 | |
| D.CO | ELECTRICAL | | | | |
| D50 | ELECTRICAL WORK | 1 LS | 203,532 | 203,532 | |
| 16000 16000 | ELECTRICAL WORK SECURITY SYSTEM WORK | 1 LS | 203,332 77,374 | 77,374 | |
| D50 | ELECTRICAL | | VISION TOTAL | 280,906 | |
| | | | | | |
| F20 | SELECTIVE BUILDING DEMOLITION | | | | |
| 02000 | DEMO FLOOR STRUCTURE | 1 LS | 18,000 | 18,000 | |
| | @ ESCALAT | | | | |
| 02000 | DEMO-CONC RAMP/DOCK | 1 LS | 7,500 | 7,500 | |
| | @ LOE | | 2 525 | 0.500 | |
| 02000 | DEMO-CONC S.O.G. | 1 LS | 2,500 | 2,500 | |
| | | | | | |

| ITEM | DESCRIPTION | | QUANTITY UNIT | UNIT COST 2 | 00 79764 8 | \$/SF |
|----------|-------------------------------|-----------------|---------------|-------------|-------------------|-------|
| | | @ ADA ELEV | | | | |
| 02000 | DEMO-STOREFRONT | @ / .S. / ESS 1 | 1 LS | 1,500 | 1,500 | |
| | | @ 2ND FLR | | | 05.000 | |
| 02000 | MISC. DEMO/PROTECT EXST'G | | 1 LS | 25,000 | 25,000 | |
| 00000 | REROUTE MECH FOR ESCALATOR | ALLOW | 1 LS | 20,000 | 20,000 | |
| 02000 | REROUTE INJECTI FOR ESCALATOR | ALLOW | , 20 | 20,000 | , | |
| 02000 | REROUTE MECH FOR LOBBY | | 1 LS | 35,000 | 35,000 | |
| | | ALLOW | 4.5 | 40.000 | 40.000 | |
| 02000 | SAWCUT DEMO CMU WALLS | | 1 LS | 10,000 | 10,000 | |
| F20 | SELECTIVE BUILDING DEMOLITION | | DIV | ISION TOTAL | 119,500 | |
| <u> </u> | | | ESTIMAT | E SUBTOTAL | 2,588,579 | |



PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION - PEDESTRIAN PLAZA/ EXTERIOR WORK

LOCATION: SEATTLE, WA

BLDG SF:

ESTIMATE: 2007096

EST TYPE: COST MODEL

| DIVISION | DESCRIPTION | | TOTAL | \$/SF |
|----------|---------------------------------------|--------|-----------|-------|
| B20 | EXTERIOR CLOSURE | | 291,945 | |
| D20 | PLUMBING | | 9,412 | |
| D50 | ELECTRICAL | | 111,811 | |
| G10 | SITE PREPARATION | | 77,375 | |
| G20 | SITE IMPROVEMENTS | | 210,753 | |
| G30 | SITE CIVIL / MECHANICAL UTILITIES | | 25,000 | |
| | ESTIMATE SUBTOTAL | | 726,296 | |
| | DESIGN CONTINGENCY @ | 12.00% | 87,156 | |
| | SUBTOTAL | | 813,452 | |
| | GENERAL CONTRACTOR'S OH & P @ | 8.00% | 65,076 | |
| | SUBTOTAL | | 878,528 | |
| | ESCALATION TO 06-JAN-09 (10.00%/YR) @ | 15.64% | 137,435 | |
| | TOTAL | | 1,015,963 | |

EXCLUSIONS:

SEE ESTIMATE SUMMARY

PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION - PEDESTRIAN PLAZA/ EXTERIOR WORKO7-0618

LOCATION: SEATTLE, WA

BLDG SF:

ESTIMATE: 2007096

EST TYPE: COST MODEL

| ITEM | DESCRIPTION | | QUANTITY UNIT | UNIT COST | TOTAL | \$/SF |
|---------------------|--|--------------|---------------|-------------|---------|-------|
| B20 | EXTERIOR CLOSURE | | | | | |
| 04850 | SEISMIC PINNING @ MASONRY | | 1 LS | 135,000 | 135,000 | |
| 04000 | oziolilo i ilitimo e ilitimo il ili | ALLOW | | | | |
| 04910 | CRACK REPAIR ALLOWANCE | | 32,250 SFA | 1.50 | 48,375 | |
| 04910 | TUCKPOINT MASONRY | | 8,062 SF | 10.00 | 80,620 | |
| | | ASSUMING 25% | _ | | 07.050 | |
| 04930 | CLEAN/SEAL EXT. MASONRY | | 13,975 SF | 2.00 | 27,950 | |
| B20 | EXTERIOR CLOSURE | | DIV | ISION TOTAL | 291,945 | |
| D20 | PLUMBING | | | | | |
| 15400 | PLUMBING/DRAINAGE ALLOWANCE | | 1 LS | 9,412 | 9,412 | |
| D20 | PLUMBING | | | ISION TOTAL | 9,412 | |
| DEA | FLECTRICAL | | | | | |
| D50 | ELECTRICAL OF OUR TY OVER THE COMMERCE. | | 1 LS | 35,000 | 35,000 | |
| 16000 | SECURITY SYSTEMS/CAMERAS | ALLOW | 1 Lo | 33,000 | 33,000 | |
| 16000 | SITE LIGHTING ALLOWANCE | ALLOW | 1 LS | 76,811 | 76,811 | |
| D50 | ELECTRICAL | | | ISION TOTAL | 111,811 | |
| D 00 | LLLOTTIONL | | 2 | | , | |
| G10 | SITE PREPARATION | | | | | |
| 02000 | ALLOW-RELOCATE MECH EQUIP | | 1 LS | 35,000 | 35,000 | |
| 02000 | DEMO-CONC SLAB @ PLAZA | | 3,650 SF | 7.50 | 27,375 | |
| 02000 | MISC. SITE DEMOLITION | | 1 LS | 10,000 | 10,000 | |
| 02000 | SAWCUTTING ALLOWANCE | | 1 LS | 5,000 | 5,000 | |
| G10 | SITE PREPARATION | | DIV | ISION TOTAL | 77,375 | |
| G20 | SITE IMPROVEMENTS | | | | | |
| 02620 | DRAINAGE MEMBRANE SYSTEM | | 3,650 SF | 7.50 | 27,375 | |
| 02755 | CONC LIGHT BASES | | 12 EA | 1,200 | 14,400 | |
| 02775 | CONC SLAB @ PLAZA/SUB-BASE | | 3,650 SF | 10.00 | 36,500 | |
| 02780 | CONC PAVERS @ PLAZA | | 1,674 SF | 22.00 | 36,828 | |
| 02780 | STONE PAVERS @ PLAZA/ENTRY RAMP | | 630 SF | 55.00 | 34,650 | |
| 02800 | REPAIR GRANITE PILLARS | | 2 EA | 2,500 | 5,000 | |
| 02820 | ARCH SCREENWALLS-ALLOW | | 150 LF | 210 | 31,500 | |
| 02830 | CONC PLANTER/SEAT WALLS | | 6 EA | 3,500 | 21,000 | |
| 10350 | FLAGPOLE W/BASE | | 1 EA | 3,500 | 3,500 | |
| G20 | SITE IMPROVEMENTS | | DIV | ISION TOTAL | 210,753 | |
| | OUTE ON WE CAREOUANION LUTHUTION | | | | | |
| G30 | SITE CIVIL / MECHANICAL UTILITIES | | | | | |
| G30 02630 | STE CIVIL / MECHANICAL UTILITIES STORM DRAINAGE ALLOWANCE | | 1 LS | 25,000 | 25,000 | |

| ITEM | DESCRIPTION | QUANTITY UNIT | UNIT COST 2007 DOMES | \$/SF |
|------|---------------------------------------|---------------|----------------------|-------|
| | | | | |
| | | | | |
| | | | | |
| | · · · · · · · · · · · · · · · · · · · | FOTIMATI | CURTOTAL 72C 20C | |
| | | ESTIMATE | SUBTOTAL 726.296 | |



PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION - RAMP/LOADING DOCK & TUNNEL

LOCATION: SEATTLE, WA

BLDG SF:

ESTIMATE: 2007096

EST TYPE: COST MODEL

| DIVISION | DESCRIPTION | TOTA | _ \$/SF |
|----------|---------------------------------------|----------------|---------|
| A10 | FOUNDATIONS | 406,14 | 3 |
| A20 | BASEMENT CONSTRUCTION | 1,008,39 | 1 |
| B20 | EXTERIOR CLOSURE | 58,02 |) |
| C10 | INTERIOR CONSTRUCTION | 81,16 |) |
| C30 | INTERIOR FINISHES | 5,00 |) |
| D20 | PLUMBING | 54,19 | 3 |
| D30 | HVAC | 60,23 | 9 |
| D40 | FIRE PROTECTION | 131,49 | 7 |
| D50 | ELECTRICAL | 266,83 |) |
| E10 | EQUIPMENT | 42,00 |) |
| E20 | FURNISHINGS | 5,00 |) |
| G10 | SITE PREPARATION | 1,000,560 |) |
| G20 | SITE IMPROVEMENTS | 388,37 | 3 |
| G30 | SITE CIVIL / MECHANICAL UTILITIES | 40,000 |) |
| G90 | OTHER SITE CONSTRUCTION | 7,500 | |
| | ESTIMATE SUBTOTAL | 3,554,91 | 1 |
| | DESIGN CONTINGENCY @ | 12.00% 426,590 |) |
| | SUBTOTAL | 3,981,503 | 3 |
| | GENERAL CONTRACTOR'S OH & P @ | 8.00% 318,520 |) |
| | SUBTOTAL | 4,300,023 | |
| | ESCALATION TO 06-JAN-09 (10.00%/YR) @ | 15.64% 672,689 |) |
| | TOTAL | 4,972,71 | 2 |

EXCLUSIONS:

SEE ESTIMATE SUMMARY

PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION - RAMP/LOADING DOCK & TUNNEL 2007-0618

LOCATION: SEATTLE, WA

BLDG SF:

ESTIMATE: 2007096

EST TYPE: COST MODEL

| ITEM | DESCRIPTION | | QUANTITY UNIT | UNIT COST | TOTAL | \$/SF |
|----------------|--------------------------------------|-----------|---------------|------------|-----------|-------|
| A10 | FOUNDATIONS | | | | | |
| 02315 | FNDTN EXCVTE/BACKFILL | | 14,326 SFA | 4.00 | 57,304 | |
| 02480 | UNDERPIN EX'STNG RET. WALL | | 265 LF | 185 | 49,025 | |
| 02740 | ASPHALT OVERLAY | | 14,326 SF | 1.50 | 21,489 | |
| 03300 | CONC BASE SLAB/GRAVEL- 6" | | 14,326 SF | 8.00 | 114,608 | |
| 03300 | FOOTINGS/FOUNDATIONS | | 14,326 SFA | 10.00 | 143,260 | |
| 03300 | RAISED LOADING DOCK/RAMP PREMIUM | | 1,490 SF | 10.00 | 14,900 | |
| 07100 | FOOTING DRAINAGE | | 556 LF | 10.00 | 5,560 | |
| A10 | FOUNDATIONS | | | SION TOTAL | 406,146 | |
| A20 | BASEMENT CONSTRUCTION | | | | | |
| | | | | | 00.000 | |
| 03310 | CIP CONC COLUMNS- 30" DIA | | 80 LF | 260 | 20,800 | |
| 03310 | CIP TUNNEL WALL- 1'4" | | 10,564 SF | 35.00 | 369,740 | |
| 03310 | TUNNEL CONC LID STRUCTURE | | 14,326 SF | 36.00 | 515,736 | |
| 03930 | WORK @ TRANSITION TO EXISTING TUNNEL | | 1 LS | 15,000 | 15,000 | |
| 07400 | DDAINIA OF MEMBRANE O MANAGEM | ALLOW | | | | |
| 07100 | DRAINAGE MEMBRANE @ WALLS/LID | | 24,890 SF | 3.50 | 87,115 | |
| A20 | BASEMENT CONSTRUCTION | | DIVI | SION TOTAL | 1,008,391 | |
| B20 | EXTERIOR CLOSURE | | | | | |
| 03370 | AIR DISCHARGE STRUCTURE/LOUVERS | | 1 LS | 19,020 | 19,020 | |
| | | ALLOW | . 20 | 10,020 | .0,020 | |
| 08330 | COILING DOORS | , 122011 | 2 EA | 12,000 | 24,000 | |
| 09220 | EXT FINISH @ TUNNEL ENTRANCE | | 1 LS | 15,000 | 15,000 | |
| | | ALLOW | 1 20 | 10,000 | 10,000 | |
| B20 | EXTERIOR CLOSURE | , (2.2.7) | DIVI | SION TOTAL | 58,020 | 18 AU |
| C10 | INTERIOR CONCERNATION | | | | | |
| | INTERIOR CONSTRUCTION | | 0.000.00 | | 74.000 | |
| 04220 | INT. CMU PLAIN 8"-SOLID GROUT | | 3,230 SF | 22.00 | 71,060 | |
| 08110 | INT. H.M. DOOR/FRM/HDWRE-SGL | | 3 LVS | 1,200 | 3,600 | |
| 08110 10000 | INT. H.M. RELITE/GLAZING | | 3 EA | 500 | 1,500 | |
| | MISC SPECIALTIES | | 1 LS | 5,000 | 5,000 | |
| C10 | INTERIOR CONSTRUCTION | | DIVI | SION TOTAL | 81,160 | |
| C30 | INTERIOR FINISHES | | | | | |
| 06200 | MISC. FINISHES/TRIM | | 1 LS | 5,000 | 5,000 | |
| C30 | INTERIOR FINISHES | | | SION TOTAL | 5,000 | |
| D20 | PLUMBING | | | | | |
| 15400 | PLUMBING | | 1 LS | E4 400 | EA 100 | |
| | PLUMBING | | | 54,198 | 54,198 | |
| D20 | FLUIVIDING | | DIVI | SION TOTAL | 54,198 | |

| ITEM | DESCRIPTION | QUANTITY UNIT | UNIT COST 2 | 00 7.0%1 8 | \$/SF |
|----------------|--|---------------|---------------|-------------------|-------|
| | | | _ _ | 001-0010 | |
| | | | | | |
| D30 | HVAC | | | | |
| 15700 | HVAC WORK | 1 LS | 60,239 | 60,239 | |
| D30 | HVAC | | SION TOTAL | 60,239 | |
| D30 | IIVAC | DIVI | OION TOTAL | 00,200 | |
| | | | | | |
| D40 | FIRE PROTECTION | | | | |
| 15300 | FIRE PROTECTION | 1 LS | 131,497 | 131,497 | |
| D40 | FIRE PROTECTION | DIVI | SION TOTAL | 131,497 | |
| | | | | | |
| D50 | ELECTRICAL | | | | |
| 16000 | ELECTRICAL WORK | 1 LS | 239,000 | 239,000 | · |
| 16000 | SECURITY SYSTEMS | 1 LS | 27,830 | 27,830 | |
| D50 | ELECTRICAL | | SION TOTAL | 266,830 | |
| | | 2 | | , | |
| | | | | | |
| E10 | EQUIPMENT | | | | |
| 11000 | MISC EQUIPMENT ALLOWANCE | 1 LS | 10,000 | 10,000 | |
| 11160 | TRUCK DOCK LEVELER | 4 EA | 8,000 | 32,000 | |
| E10 | EQUIPMENT | DIVI | SION TOTAL | 42,000 | |
| | | | | | |
| E20 | FURNISHINGS | | | | |
| 12320 | CASEWORK/SHELVING ALLOWANCE | 1 LS | 5,000 | 5,000 | |
| E20 | FURNISHINGS | | SION TOTAL | 5,000 | |
| | | 5 | | 0,000 | |
| | | | | | |
| G10 | SITE PREPARATION | | | | |
| 02000 | ALLOW-REWORK @ FUEL TANK | 1 LS | 15,000 | 15,000 | |
| 02000 | DEMO/SALVAGE BRICK PAVERS | 2,700 SF | 2.50 | 6,750 | |
| 02000 | DEMO-ASPHALT @ FIRE LANE | 2,550 SF | 5.00 | 12,750 | |
| 02000 | DEMO-EXISTING TUNNEL STRUCTURE | 1 LS | 40,000 | 40,000 10,000 | |
| 02000 02000 | MISC SAWCUT/PROTECT EXST'G REMOVE ROLLUP DOORS | 1 LS 2 EA | 10,000 500 | 1,000 | |
| 02000 | SITE DEMO ALLOWANCE | 57,000 SFA | 1.00 | 57,000 | |
| 02250 | SHORING ALLOWANCE (2 SIDES) | 5,282 SF | 55.00 | 290,510 | |
| 02315 | BACKFILL @ TUNNEL-FROM STOCKPILE | 7,200 CY | 15.00 | 108,000 | |
| 02315 | EXCAVATE/STOCKPILE FOR TUNNEL/RAMP | 15,600 CY | 18.00 | 280,800 | |
| 02315 | RAISE SITE WITH STOCKPILED SOIL | 8,400 CY | 15.00 | 126,000 | |
| 02335 | GRADE/COMPACT SITE | 57,000 SF | 0.75 | 42,750 | |
| 02370 | EROSION CONTROL | 1 LS | 10,000 | 10,000 | |
| G10 | SITE PREPARATION | DIVI | SION TOTAL | 1,000,560 | |
| | | | | | |
| G20 | SITE IMPROVEMENTS | | | | |
| 02740 | REPAVE FIRE LANE | 2,550 SF | 6.75 | 17,213 | |
| 02740 | RESET BRICK PAVERS, GROUTED | 2,700 SF | 9.00 | 24,300 | |
| 02820 | ALLOW-RENOVATE SITE STAIR | 1 LS | 7,500 | 7,500 | |
| 02820 | RENOVATE EXISTING CONC/BRICK WALL | 180 LF | 300 | 54,000 | |
| 02830 | RETAINING WALLS @ RAMP | 3,840 SF | 45.00 | 172,800 | |
| 02830 | SITE RETAINING WALLS | 804 LF | 140 | 112,560 | |
| | | | | | |

| ITEM | DESCRIPTION | | QUANTITY UNIT | UNIT COST2 | 007 19641 8 | \$/\$ |
|-------|-----------------------------------|-------|---------------|-------------|--------------------|-------|
| G20 | SITE IMPROVEMENTS | | DIV | SION TOTAL | 388,373 | |
| G30 | SITE CIVIL / MECHANICAL UTILITIES | | | | | |
| 02630 | STORM COLLECTION/DRAINAGE | ALLOW | 1 LS | 40,000 | 40,000 | |
| G30 | SITE CIVIL / MECHANICAL UTILITIES | | DIVI | ISION TOTAL | 40,000 | |
| G90 | OTHER SITE CONSTRUCTION | | | | | |
| 02770 | CURBS | | 300 LF | 25.00 | 7,500 | |
| G90 | OTHER SITE CONSTRUCTION | | DIV | ISION TOTAL | 7,500 | |
| | | | ESTIMATI | E SUBTOTAL | 3,554,914 | |

PROJECT: KING COUNTY COURTHOUSE SOUTH ENTRY RENOVATION 2007-0618

LOCATION: SEATTLE, WA **ESTIMATE:** 2007096

EST TYPE: COST MODEL

ALT#

REVOLVING DOORS @ 3RD/4TH ST. EXITS

| ITEM | DESCRIPTION | | QUANTITY UNIT | UNIT COST | TOTAL |
|-------|------------------------------|-------|---------------|-----------|---------|
| 05100 | STRUCTURE FRAME AROUND DOORS | | 2 LS | 7,500 | 15,000 |
| | | ALLOW | | | |
| 08340 | REVOLVING DOORS | | 2 EA | 70,000 | 140,000 |
| 09250 | WALL/FINISHES AROUND DOOR | | 2 LS | 12,500 | 25,000 |
| | | ALLOW | | | • |
| | | ALTER | NATE SUBTOTAL | | 180,000 |
| | | | MARKUP @ | 39.9% | 71,789 |
| | | | TOTAL | | 251,789 |

ALT# 2 ADDITIONAL STOP @ ADA ELEVATOR

| ITEM | DESCRIPTION | QUANTITY UNIT | UNIT COST | TOTAL |
|-------|-------------------------------|--------------------|-----------|--------|
| 04220 | ELEVATOR SHAFT WALL | 666 SF | 22.00 | 14,652 |
| 09380 | DEMO/REPLACE WALLS & FINISHES | 1 LS | 20,000 | 20,000 |
| | | ALLOW | | |
| 14240 | ADA ELEVATOR-ADDITIONAL STOP | 1 LS | 10,000 | 10,000 |
| | | ALTERNATE SUBTOTAL | | 44,652 |
| | | MARKUP @ | , 39.9% | 17,808 |
| | | TOTAL | | 62,460 |

ALT # 3 USE GRANITE @ ALL INFILL PANELS @ PLAZA

| ITEM | DESCRIPTION | QUANTITY UNIT | UNIT COST | TOTAL |
|-------|-----------------------------------|--------------------|-----------|---------|
| 02780 | CONC PAVERS @ PLAZA | -1,674 SF | 22.00 | -36,828 |
| 02780 | GRANITE PAVERS @ PLAZA/ENTRY RAMP | 1,674 SF | 55.00 | 92,070 |
| | | ALTERNATE SUBTOTAL | | 55,242 |
| | | MARKUP @ | 39.9% | 22,032 |
| | | TOTAL | | 77,274 |

\$16,476,081

2008 CIP PROJECT COST ESTIMATE SUMMARY DESIGN DEVELOPMENT OPTION - 1

| Project Name: | Courthouse South Entry | CIP Number: | | Date: | 1-Nov-07 |
|---|--|---------------|-------------------------|----------------|---------------------------------------|
| Requesting Agency: | | Estimator: | Seneca - FMD | | |
| Implementing Agency: Project Scope: | This project restores the south e | Checked by: | rance to the Courthouse | An underground | loading facility |
| тојест осоре: | will be constructed at the Jefferso | | | | |
| | park will be redone and funded b | | • | J | |
| | New security entry point equipme | | | | |
| | only. No new exit only doors are Lobby exit. Also included is the a | | | | |
| | | | ******************* | | |
| | | | TOTAL PROJECT | | 2008 PROJECT |
| ELEMENT - DESCRIPTIO | N | | COST | | REQUEST |
| 001 - CONSULTANT DES | IGN | | **** | | ** |
| Basic A/E Fee Landmark Commission | preparation & review | | \$978,000 inc | _ | \$0 |
| Security Consultant | preparation & review | | inc | | |
| Elevator Consultant | | | inc | | |
| Grading Permit/SWM D | Orainage Review | | na | _ | |
| Level II Drainage Tech. | . Report | | na | _ | |
| Soils Testing | | | \$10,000 | _ | |
| Outside Survey | | | na | _ | |
| Consultant Selection A PCSP Division Costs (| | | inc | | |
| Asbestos Assessment | , rocurement, | | \$5,000 | _ | |
| Other Design | | | 40,000 | _ | |
| Total 001 - Consultant De | sign Cost | | \$993,000 | | \$993,000 |
| 003 - CONSTRUCTION | | | | | |
| | | | | | |
| MAX. ALLOWABLE CONS | , , | | \$ 10,797,807 | | \$0 |
| Sales Tax(| 8.90%)of MACC | | \$961,005 | _ | \$0 |
| Building Permit Fees(| 2.00%)of MACC | | \$215,956 | | \$0 \$0 |
| Data Communications Cos Telephone Cost (\$350/phor | | | \$8,000 \$950 | _ | - 40 |
| Relocation/Temporary Con | | | \$50,000 | | |
| | ruction (required for work in CH, RJC & K | CCF) | \$60,000 | _ | |
| Artist Designs & Implemen | tation (applicable WSST included) | , | | _ | \$0 |
| Moving Cost | | | \$10,000 | _ | |
| PCSP Division review and | | | | | |
| Printing Cost (Bid Docume | | | \$20,000 | _ | |
| Special Inspection & Testin | ng ree | | \$50,000 | _ | |
| Total 003 - Construction | Cost | | \$12,173,718 | | \$12,173,718 |
| 004 - EQUIPMENT & FUR | RNISHINGS | | | | · · · · · · · · · · · · · · · · · · · |
| Total 004 - Equipment & I | Furnish. Cost | | \$328,142 | | \$328,142 |
| Miscellaneous | | 0 |) | | |
| 005 - CONTINGENCY | | *** | | | |
| Project Conting. (| 15.00%) of 001, 003, 004,007, | & 009 | | _ | |
| Total 005 - Contingency (| Cost | | \$2,086,479 | | \$2,086,479 |
| 007 - COUNTY FORCE DE | | | | _ | |
| Project Design (| of 001, 003, 004) | | | | ** |
| Other | | | \$0 | _ | \$0 |
| Total 007 - CONTRACTED | CONST. MGMT. | | | | |
| Includes cost estimating | | | \$400,000 | | \$400,000 |
| | | • | | | |
| GGCIP Project Mgmt | DMINISTRATION Hours | 150 | | | |
| Total 009 - County Force | | 130 | \$15,000 | | \$15,000 |
| Total our - occiny i orce | Admin. Cost | | \$10,000 | _ | <u> </u> |
| 006 - ART (1% of 001,003, | ,005,007 & 009) | | \$156,682 | | \$156,682 |
| 040 ADMINISTRATION | M | ! | 4055.553 | _ | 4000 555 |
| 010 - ADMINISTRATIVE C | OH (2.00% of total) | project cost) | \$323,060 | <u> </u> | \$323,060 |
| LILLENSTON SELECTION CONTRACTOR | 220.00.20.0 | | | | |
| TOTAL PROJECT CO | ST | | \$16,476,081 | | \$16,476,081 |
| Less Existing Fund | ds: | 0 | | | |

2008 PROJECT REQUEST

\$8,526,954

2008 CIP PROJECT COST ESTIMATE SUMMARY DESIGN DEVELOPMENT OPTION - 2

2008 PROJECT REQUEST

| Project Name: | Courthouse South Entry | CIP Number: | | Date: | 1-Nov-07 |
|---|--|---|--|---|-----------------------------------|
| Requesting Agency: | | Estimator: | Seneca - FMD | | |
| Implementing Agency: | | Checked by: | | | |
| Project Scope: | This project restores the south entry and there are no improvements to the New security entry point equipment is | e existing tunnel. s included - it is as | The park will be redone ssumed the 3rd and 4th | and funded by the Avenue entrances v | City of Seattle. vill become exit |
| | only. Existing doors at 3rd & 4th Ave exit only. Also included is the an AD | | • | | new South Lobby |
| | | | | | |
| | | | TOTAL PROJECT | | 2008 PROJECT |
| ELEMENT - DESCRIPTIO | N | | COST | <u> </u> | REQUEST |
| 001 - CONSULTANT DES | | | | | |
| Basic A/E Fee Landmark Commission | propagation & ravious | | \$480,000 inc | | \$0_ |
| Security Consultant | preparation of review | | inc | _ | |
| Elevator Consultant | | | inc | | |
| Grading Permit/SWM (| | | na | _ | |
| Level II Drainage Tech Soils Testing | . кероп | | na \$0 | _ | |
| Outside Survey | | | na | _ | |
| Consultant Selection A | | | inc | | |
| PCSP Division Costs Asbestos Assessment | | | \$5,000 | | |
| Other Design | | | | _ | |
| Total 001 - Consultant De | esign Cost | | \$485,000 | | \$485,000 |
| 003 - CONSTRUCTION | | | | | |
| MAX. ALLOWABLE CONS | ST COST (MACC) | | \$ 5,347,714 | - | \$0 |
| Sales Tax(| 8.90%)of MACC | | \$475,947 | _ | \$0 |
| Building Permit Fees(| 2.00%)of MACC | | \$106,954 | _ | \$0 |
| Data Communications Cost | | | \$8,000 | | \$0 |
| Telephone Cost (\$350/pho Relocation/Temporary Cor | | | \$950 \$25,000 | _ | |
| Security Cost during Cons | truction (required for work in CH, RJC & KCC | F) | \$60,000 | _ | |
| | itation (applicable WSST included) | | \$10,000 | _ | \$0_ |
| Moving Cost PCSP Division review and | Bid Advertisement Costs | | \$10,000 | _ | |
| Printing Cost (Bid Docume | ents) | | \$20,000 | _ | |
| Special Inspection & Testi | ng Fee | | \$25,000 | _ | |
| Total 003 - Construction | Cost | | \$6,079,565 | | \$6,079,565 |
| 004 - EQUIPMENT & FUI | | | | | |
| Total 004 - Equipment & Miscellaneous | Furnish. Cost | | \$328,142 0 | L. | \$328,142 |
| 005 - CONTINGENCY | | | | | |
| Project Conting. (| 15.00%) of 001, 003, 004,007, & 0 | 009 | | _ | |
| Total 005 - Contingency | Cost | | \$1,080,031 | | \$1,080,031 |
| 007 - COUNTY FORCE D | ESIGN | | | | |
| | (of 001, 003, 004) | | | _ | |
| Other | | | \$0 | _ | \$0 |
| Total 007 - CONTRACTE | D CONST. MGMT. | | | _ | |
| Includes cost estimating | | | \$300,000 | | \$300,000 |
| 009 - COUNTY FORCE A | DMINISTRATION | | | | |
| GGCIP Project Mgmt | Hours | 150 | | _ | 47.500 |
| Total,009 - County Force | Admin. Cost | | \$7,500 | L. | \$7,500 |
| 006 - ART (1% of 001,003 | 3,005,007 & 009) | | \$79,521 | | \$79,521 |
| A40 ADMINISTRATIO | | 44) | 445-15-7 | | 9497 404 |
| 010 - ADMINISTRATIVE (| OH (2.00% of total proje | ect cost) | \$167,195 | <u>L</u> | \$167,195 |
| TOTAL PROJECT CO | ST . | | \$8,526,954 | <u> </u> | \$8,526,954 |
| Less Existing Fund | - \ | 0 | | <u></u> | |

2008 CIP PROJECT COST ESTIMATE SUMMARY **DESIGN DEVELOPMENT OPTION - 3** 2-Nov-07 Date Courthouse South Entry CIP Number: Project Name: Seneca - FMD Requesting Agency: Estimator Implementing Agency: Checked by: This project restores the south entry as the primary entrance to the Courthouse. An underground loading facility Project Scope: will be constructed at the Jefferson Street ROW face of the exiting tunnel to accommodate loading functions. The park will be redone and funded by the City of Seattle. New security entry point equipment is included - it is assumed the 3rd and 4th Avenue entrances will become exit only. New exit only doors are included for the existing 3rd and 4th Avenue, and the new South Lobby exit. Also included is the an ADA Elervator to the 2nd Floor, and Granite Paving in the Plaza 2008 **PROJECT** PROJECT REQUEST COST ELEMENT - DESCRIPTION 001 - CONSULTANT DESIGN \$978,000 Basic A/E Fee inc Landmark Commission preparation & review Security Consultant inc inc Elevator Consultant Grading Permit/SWM Drainage Review na na Level II Drainage Tech. Report \$10,000 Soils Testing na Outside Survey Consultant Selection Advertisement Costs PCSP Division Costs (Procurement) \$5,000 Asbestos Assessment Other Design \$993,000 \$993,000 Total 001 - Consultant Design Cost 003 - CONSTRUCTION 11,049,596 MAX. ALLOWABLE CONST. COST (MACC) 8.90%)of MACC \$983,414 Sales Tax.....(__ \$220,992 Building Permit Fees..(2.00%)of MACC \$8,000 Data Communications Costs \$950 Telephone Cost (\$350/phone) \$50,000 Relocation/Temporary Construction Cost \$60,000 Security Cost during Construction (required for work in CH, RJC & KCCF) Artist Designs & Implementation (applicable WSST included) \$10,000 Moving Cost PCSP Division review and Bid Advertisement Costs \$20,000 Printing Cost (Bid Documents) \$50,000 Special Inspection & Testing Fee \$12,452,952 Total 003 - Construction Cost \$12,452,952 004 - EQUIPMENT & FURNISHINGS \$328,142 \$328,142 Total 004 - Equipment & Furnish. Cost Miscellaneous 005 - CONTINGENCY 15.00%) of 001, 003, 004,007, & 009 \$2,128,364 \$2,128,364 Total 005 - Contingency Cost 007 - COUNTY FORCE DESIGN of 001, 003, 004) Project Design Other Total 007 - CONTRACTED CONST. MGMT. \$400,000 \$400,000 Includes cost estimating 009 - COUNTY FORCE ADMINISTRATION 150 GGCIP Project Mgmt \$15,000 \$15,000 Total 009 - County Force Admin. Cost \$159,893 \$159,893 006 - ART (1% of 001,003,005,007 & 009) \$329,547 \$329,547 010 - ADMINISTRATIVE OH (2.00% of total project cost) \$16,806,898 TOTAL PROJECT COST \$16,806,898 Less Existing Funds: \$16,806,898 2008 PROJECT REQUEST SOURCE OF FUNDING TOTAL


| No. 2 at No. 2 at | | | - Cur | 2 Abumban | | Date: | 1-Nov-0 |
|--|---|-----------------|--|------------------------------|---|--|--|
| roject Name: | Courthouse Sout | th Entry | UIF | Number: | | Date: | 1=1107-0 |
| equesting Agency: | | | | | neca - FMD | | |
| nplementing Agency: | This replact of | | Ch | ecked by: | nce to the Courthous | No loading (| lock is constructed |
| roject Scope: | I his project it | estores the a | Outn entry as the printing |)⊓mary eπασι α tunnel The | nce to the Courthous e park will be redone | e. Invioading o | the City of Seattle. |
| + | New security 6 | entry point e | nents to the existing | g turner ad - it is assur | med the 3rd and 4th | Avenue entranc | es will become exit |
| 1 | - New exit | anny pome : | are included for the | o 3rd and 4th | Avenue entrances, | and the new Sou | uth Lobby exit. Also |
| | | | | | nite Paving inthe Pla | | Au. 222., |
| | 7"" |) ((11) | 71 TULO: 10 | 100,0 | Into . 2 5 | | |
| | 1 | | | | | | Anne |
| | - | | | | TOTAL | | 2008 PROJECT |
| LEMENT - DESCRIPTION | + | | | | PROJECT | - | REQUEST |
| LEMENT - DESCRIPTION - CONSULTANT DE | | | | | - COSI | <u> </u> | A PER CONTRACTOR OF THE PROPERTY OF THE PROPER |
| asic A/E Fee | J | | | | \$480,000 | | |
| Landmark Commission | n preparation & rev | view | | inc | : | | |
| Security Consultant | | | | inc | | \rightarrow | |
| Elevator Consultant | 7 | | | inc | | | |
| Grading Permit/SWM | | | | na na | | | |
| Level II Drainage Tec Soils Testing | h. Report | | | | | <u> </u> | |
| Outside Survey | + | | | na | | | |
| Consultant Selection | | its | | inc | | 1 | |
| PCSP Division Costs | (Procurement) | | | | | \Box | |
| Asbestos Assessmen | t | _ | | | \$5,000 | | |
| Other Design otal 001 - Consultant D | Coet | | | | \$485,000 | - | \$485,00 |
| otal 001 - Consum | Jesign Cost | | | | 3400,000 | | |
| 03 - CONSTRUCTION | 1 | | | | | | |
| | | | | | | | |
| AX. ALLOWABLE CON | | | | \$_ | 5,599,503 | | |
| ales Tax(| | of MACC | - | | \$498,356 \$111,990 | | |
| uilding Permit Fees(| | of MACC | | | \$111,990 \$8,000 | + | |
| Pata Communications Co Telephone Cost (\$350/ph | | | | | \$8,000 | | |
| telocation/Temporary Co | | | | | \$25,000 | | |
| ecurity Cost during Con | struction (required t | | | | \$60,000 | | |
| Artist Designs & Impleme | ntation (applicable | WSST includ | ed) | | | | |
| Moving Cost | | | | | \$10,000 | | |
| Printing Cost (Bid Docum | | nt Costs | - | | \$20,000 | - | |
| Printing Cost (Bid Docum Special Inspection & Tes | | | | | \$25,000 | + | |
| | | | | | | | |
| Total 003 - Construction | 1 Cost | | | | \$6,358,799 | | \$6,358,79 |
| 0 EI | 1 | | | | | | |
| 004 - EQUIPMENT & FL Total 004 - Equipment 8 | | | <u> </u> | | \$328,142 | | \$328,14 |
| Miscellaneous | Futman. 555. | | | 0 | #320, | | |
| Whocoman | + | | | | | | |
| 05 - CONTINGENCY | | | | | | | |
| Project Conting. (| | of 001, 003, | 004,007, & 009 | | ********* | | \$1 121 0 |
| Total 005 - Contingency | Cost | | - | | \$1,121,916 | | \$1,121,9 |
| 007 - COUNTY FORCE I | PEGICN | | | | | | |
| Project Design | | of 001, 003, 00 |)4) | | | | |
| Other | 1 | | | | | | |
| | | | <u> </u> | | | | <u> </u> |
| Includes cost estimate | | · | | | \$300,000 | - | \$300,00 |
| Includes cost community | ng T | | | <u>_</u> | #300,000 | | |
| 009 - COUNTY FORCE | ADMINISTRATION | | | | | | |
| GGCIP Project Mgmt | H | Hours | 150 | | | | 47.5 |
| Total 009 - County Forc | e Admin. Cost | | | | \$7,500 | | \$7,50 |
| -5004.00 | | | | - | A00 700 | | \$82,7 |
| 006 - ART (1% of 001,00 | 3,005,007 & 009 | | | | \$82,732 | | |
|)10 - ADMINISTRATIVE | OH (| 2.00% | of total project cost) | | \$173,682 | | \$173,6 |
| 710 - 7.12 | Ť | | 0, | | | | |
| | Ţ | | | | | | |
| TOTAL PROJECT C | OST | | | 10 | \$8,857,771 | | \$8,857,77 |
| Less Existing Fund | ds: | | | | | | |
| LEGG EXIGUITY I WIT | annonia anno articolori del control. Ha | =eT | | | | | \$8,857,77 |
| ermakakakakar et. 1900-bila 1900-bila | OI NEWS. | 1 01 | 朝 称 : 司を告, 石(お L | | | | Ψυ,υυ., |
| 2008 PROJE | 1 | | | | | | |
| ermakakakakar et. 1900-bila 1900-bila | | | ļ | | | | |
| 2008 PROJE | E EI INDIN | <u> </u> | | | | | |
| ermakakakakar et. 1900-bila 1900-bila | F FUNDING | G | | | | | |
| 2008 PROJE | F FUNDING | G | | | | | |
| 2008 PROJE | F FUNDING | G | | | | | |
| 2008 PROJE | F FUNDING | G | | | | | |
| 2008 PROJE | F FUNDING | G | | | | | |
| SOURCE O | F FUNDING | G | | | | | |


King County Courthouse South Entrance Renovation Report

Attachment E: King County Department of Executive Services – Facilities Management Division

Courthouse South Entry Renovation Project

- Security Layout Graphics for South Entry
- Specifications Information for New South Entry Security Screening Equipment







ExitSentry® for Aviation

Automated Monitoring for Airport Terminal Exit Lanes

ExitSentry® by Cernium is the industry-leading monitoring system that automatically watches people and object flow through airport exit lanes. This TSA-accepted, patented¹ solution has logged over one million hours of proven performance in more than 40 airports throughout North America. ExitSentry's powerful video analytics technology immediately identifies any individual attempting to enter an airport exit lane from the wrong direction. Using both audible and visual alarms, it alerts security personnel and then digitally records the incident for instant playback. ExitSentry maximizes exit lane security and enables security personnel to more efficiently and effectively handle other essential responsibilities during peak traffic times, generating a positive return on investment in a short time.

| BENEFITS | KEY FEATURES |
|--|---|
| Maximum Performance for Your Investment | Patented, field-configurable software that detects wrong-way motion of people and objects; includes anti-passback protection Compliant with rigorous TSA performance standards |
| More Productive, Preemptive Security Forces | Early warning detection and event instant replay Digital recording and storage of alarm video with time and date stamp |
| Simple and Intuitive Operation | User training in under 15 minutes User-defined pre-alarm warning zone Multi-media event logging and documentation |
| Easy Installation, Integration and Expansion | Interface to other systems and functions for remote alarm notification, intrusion containment, authorized remote bypass, or other functions Reliable equipment utilizes off-the-shelf components Accomodates variable lane widths and multi-lane configurations |




Figure 1: ExitSentry Airport Exit Lane Monitoring Solution Applies powerful video analytics technology to immediately catch any individual attempting to enter an exit lane from the wrong direction






EXITSENTRY


Photographs of Wrong-Way Motion Events

The following photographs were captured by Cernium's ExitSentry System installed in the exit lane of a major U.S. Airport. Each set of two photos, one from the "detection" camera (left side) and one from the "watcher" camera (right side), shows a wrong-way motion event in the exit lane. The "detection" camera tracks each object with a "box" and displays a "tail" representing recent frame history. The "tail" and "box" are **green** if the object is proceeding correctly and **red** once wrong-way motion has been detected.




3/14/03 3:33pm






Adult Stop & Reverse


3/20/03 1:04pm






Children Activity

3/10/03 9:34am





Rapiscan 618

Rapiscan[®] systems

An OSI Systems Company


BAGGAGE AND PARCEL INSPECTION


Compact

Secure Storage

Dual Energy

Cost Effective





The **Rapiscan 618** provides the benefits of a compact and cost effective X-ray system while still providing dual energy performance and a generous tunnel opening of 550mm (21.35 inches) wide by 360mm (14.04 inches) high.

Its innovative design includes a lockable console and folding conveyors for secure and compact storage when not in use. The **Rapiscan 618** has been designed for rapid relocation and can be wheeled through narrow doorways. The **Rapiscan 618** can be part of an effective event based security solution for hotels and convention centers.

CUSTOMER SUPPORT SERVICES

Our team is dedicated to providing a prompt, effective and personalized response that exceeds your expectations. With spare parts inventory and skilled technicians all over the world, you can be certain Rapiscan Systems will always be prepared with a solution to address your requirements. By measuring response time, parts delivery and support status, our team embraces a customer centric philosophy to ensure continual improvement of our products and services.

Features & Options


Threat Image Projection (TIP): TIP inserts digital threat images at configurable frequencies into the regular flow of bags. TIP is a reliable method for continually improving the skill level of screeners and is the preferred training method used by regulatory agencies worldwide.

Network Display Station (NDS): NDS improves threat detection, throughput, and simplifies operating procedures by enabling the operator performing a manual search of suspect bags to reconcile the actual bag contents with the scanned image.

Network Management System (NMS): Allows a supervisor to monitor the performance of many X-ray checkpoints in a large facility from a single location.

Enhanced Performance X-ray (EPX): Enables consistent detection of materials having characteristics of explosives, narcotics, gold, currency and agricultural products.

Operator Training Program (OTP): OTP enables the X-ray system to be used as a training terminal without running parcels.



Rapiscan 618

An OSI Systems Company

BAGGAGE AND PARCEL INSPECTION

PHYSICAL SPECIFICATIONS

Dimensions:

Length: 1,585 mm (61.82 in.) Unit not in use Height: 1,360 mm (53.04 in.) excluding monitor

Width: 735 mm (28.67 in.)

Tunnel Size:

550 mm (W) x 360 mm (H) (21.35 x 14.04 in.)

Conveyor Speed:

0.22 m/sec (44 ft./min)

Maximum Load:

165 Kg (365 lbs) evenly distributed Net: 412 Kg (908.3 lbs)

Approx Weight:

Gross: 500 Kg (1,102.3 lbs)

System Power:

115 VAC +/- 10% / 60Hz / 10 Amps or

230 VAC +/- 10% / 50Hz / 5 Amps

X-RAY GENERATOR AND IMAGE PERFORMANCE

Wire Resolution: Steel Penetration:

38 AWG guaranteed, 40 AWG typical 27mm guaranteed, 29 mm typical Material Separation: Low Z, Medium Z, High Z, to 0.5 accuracy

Cooling:

Sealed oil bath with forced air

Anode Voltage: **Tube Current:**

160KV rated, operating at 140KV 0.7 mA typical

Orientation:

Vertically Upward

HIGH PENETRATION OPTION (HP)

Steel Penetration: 35mm guaranteed

Wire Resolution: 38 AWG guaranteed, 40 AWG typical

Anode Voltage: 180 rated, operating at 160KV

Tube Current: 1mA

COMPUTER SPECIFICATIONS

Monitor:

Processor Speed: Intel Pentium® Processor currently available 17" XVGA color, high refresh, non-flicker

Memory:

64 MB RAM minimum

Video Memory:

16 MB minimum

Hard Disk Drive:

40 GB minimum 54X

CD-ROM Drive:

1.44 MB Floppy Disk:

Access to keyboard port and parallel port is provided by means of a lockable access panel on the outside of the machine.

OPERATING ENVIRONMENT

Storage Temperature:

-20°C to 50°C 0°C to 40°C

Operating Temperature: Relative Humidity:

5 to 95% non-condensing

HEALTH & SAFETY

All Rapiscan Systems products comply with applicable international health and safety regulations including USA FDA X-ray systems (Federal Standard 21CFR 1020.40) and Health and Safety at Work Act 1974-section 6, Amended by the Consumer Protection Act 1987. Maximum leakage radiation less than 0.1mR/hr (1µ Sv/hr) in contact with outer panels.

Film Safety: For ISO 1600/33 DIN, guaranteed up to 10 times

exposure to radiation. CE Compliance: Yes

FCC & IEC Compliance: Yes

ISO 9001:2000 Certified

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice.

1590mm (62.6in) 784mm (30,9in) 403mm (15.9ln) 560m n (22.0in) 993mm (39.1in) 735mm (28.9in) 550mm (21,4in) 1361mm (54.4m) (48.8h)

| STANDARD FEATURES | OPTIONS |
|--|------------------------------------|
| Crystal Clear™ | Flat Panel LCD Monitor |
| Multi Energy Imaging (4 color) | Threat Image Projection (TIP) |
| Density Threat Alert | TIP Network |
| Variable Edge Enhancement | Target™-Screener Assist Technology |
| High/Low Penetration | Network Display Station (NDS) |
| Variable Gamma | Network Management System (NMS) |
| Inverse Video | Power Conditioner |
| Pseudo Color | Secure Workstation |
| Variable Density Zoom | Remote Workstation |
| Organic/Inorganic Stripping | Conveyor Accessories |
| Black and White Viewing | Foot-mat |
| Variable Color Stripping | UPS (Uninterrupted Power Supply) |
| Zoom | VCR Output |
| View Previous Bag | Video Printer |
| Manual Image Archiving | Automatic Image Archiving |
| Baggage Counter | Auto Reject Unit |
| Search Indicator | High Penetration X-ray Generator |
| Date/Time Display | Foldable Conveyor |
| Full Diagnostic Built In Test Facility | Protective Tunnels |
| Operator Training Program (OTP) | |
| Enhance Performance X-ray (EPX) | |

www.rapiscansystems.com

UNITED STATES OF AMERICA

3232 W. El Segundo Blvd. Hawthorne, California 90250 UNITED STATES of AMERICA Tel: +1 310-978-1457

sales@rapiscansystems.com

Fax: +1 310-349-2491

UNITED KINGDOM

X-Ray House **Bonehurst Road** Salfords Surrey RH1 5GG UNITED KINGDOM Tel: +44 (0) 870-7774301

Fax: +44 (0) 870-7774302

ASIA PACIFIC

240 Macpherson Road #06-04 Pines Industrial Building Singapore 348574 SINGAPORE Tel: +65-6743-9892

Fax: +65-6743-9885 / 6743-9915

distributor stamp

Metor 300

Walk-Through Metal Detector

PEOPLE SCREENING

Enhanced Multi-Zone Principle

Excellent Detection and Immunity

Innovative User-Interface

Appealing Design

The **Metor 300** is a second generation true multi-zone metal detector. It offers superior performance for demanding high security applications.

SUPERIOR DETECTION AND DISCRIMINATION


Utilizing an intelligent 8Z8F architecture, the Metor 300 offers top-class performance in metal detection and unbeatable detection uniformity for metal threat objects regardless of their shape and orientation. This is achieved with an overlapping new multi-zone coil system, which combines the unique true multi-zone features with frequency distribution technology. The operating frequency distribution eliminates electromagnetic interference present at installation environments today. Together with effective digital signal process-

ing it offers excellent interference immunity.

The Metor 300 can detect multiple threat objects independently in different zones. Due to eight independent detection zones, signals from distributed harmless objects do not combine to produce unnecessary alarms. In addition, independent detection zones enable free sensitivity adjustment of each zone.

MAXIMIZE THROUGHPUT

The **Metor 300** is equipped with two integrated zone displays. These identify the level(s) at



which detected object(s) are carried. The zone displays enable security personnel to immediately target metal objects and ensure that maximum throughput can be maintained. In addition, the **Metor 300** is equipped with traffic lights (green and red) indicating when the passenger can pass through the gate.

EASY TO INSTALL, SIMPLE TO OPERATE

The Metor 300 display unit can be mounted on all four sides of the detector. This improves flexibility in installation and when operating the unit. The display unit has a 2x20 character alphanumerical display. It gives information on how to operate the unit, and also functions as a signal level indicator. In addition, the display unit has LED bars showing the zone display indication. This increases the visibility of the zone display information.

All parameters are set through a bi-directional remote control unit that enables the copying of the parameters from one unit to other units. This control unit, unique only to Metor



An OSI Systems Company

brand products, makes programming several detectors fast and easy. The menu structure of **Metor 300** resembles mobile phones' user interface and is therefore familiar to many users. Help texts in the menu further facilitate the operations. The user interface has three user levels: OPERATOR, USER and SUPERUSER. The **Metor 300** has a memory bank, which enables storing customer specific parameter settings.

VERSATILE DETECTION PROGRAMS

The Metor 300 walk-through metal detector includes preset weapon specific detection programs to meet the requirements set by internationally recognized authorities. When developing new detection programs we use electromagnetic responses from real guns and knives, and thereby the programs reflect real-life threats.

The **Metor 300** also incorporates an advanced Random Alarm function, which enables discreet search of non-alarming passengers.

ENHANCED SECURITY

To guarantee tamperproof and continuous operation, the switches, cables and connectors in the **Metor 300** are built-in, and the remote control unit can be locked inside the crosspiece. The remote control unit operation is secured with passwords and a code hopping encryption algorithm to prevent unauthorized access. The ON/OFF switches can be accessed with or without a key.

STATISTICS

Intelligent traffic and alarms counters calculate the traffic flow and resultant alarms. The counters both increment and decrement, thereby giving a true traffic count.

Options & Accessories

BATTERY BACKUP SYSTEM: For 2-hour runtime when no power is available.

METORNET 3 PRO: Remote Security Management System collects the statistics on traffic flows and alarm data of up to 255 Metor walk-through metal detectors and generates easy-to-read reports. It allows detector security levels to be changed from a central PC.

TEST PIECES: To assist in calibration and testing.

ADA COMPLIANT CROSSPIECE:

32 in. crosspieces are available to meet ADA compliance for wheel-chair accessibility.



ONE COMPANY - TOTAL SECURITY



An OSI Systems Company

Metor 300

Walk-Through Metal Detector

PEOPLE SCREENING

USA, CANADA, LATIN AMERICA

8 Commerce Way Suite 115

Robbinsville, New Jersey 08691 UNITED STATES of AMERICA

UNITED STATES of AMERIC Tel: +1 609-406-9000

Tel: +1 609-406-9000 Fax: +1 609-530-0842

Fax: +1 609-530-0842 Toll Free: 1-800-963-8676

AMERICAS

2805 Columbia Street Torrance, California 90503

UNITED STATES OF AMERICA

Tel: +1 310-978-1457 Fax: +1 310-349-2491

EUROPE, AFRICA, MID EAST

Nihtisiilankuja 5, P.O. Box 174 FIN-02631 Espoo

FIN-02631 Esp FINLAND

Tel: +358 9 32941500

Fax: +358 9 32941302

X-Ray House

Bonehurst Road

Salfords Surrey RH1 5GG

Surrey RH1 5GG UNITED KINGDOM

UNITED KINGDOM Tel: +44 (0) 870-7774301

Fax: +44 (0) 870-7774302

ASIA

240 Macpherson Road #06-04 Pines Industrial Building

Singapore 348574

SINGAPORE Tel: +65-6743-9892

Fax: +65-6743-9885

AUSTRALIA

Rapiscan House 4 Ross Street South Melbourne Victoria

Australia 3205

AUSTRALIA Tel: +61 3 9929 4601


Tel: +61 3 9929 4601 Fax: +61 3 9929 4655

E-MAIL

9150080-3

sales@rapiscansystems.com

ISO 9001:2000 Certified



| CONFORMITY | |
|----------------------------------|---|
| Safety Standards | The Metor 300 meets with the limits set by international standards for human safety. Safe for wearers of heart pacemakers, pregnant women and magnetic recording materials. |
| C € Compliant | Yes, conforms to the applicable international standards for electrical safety and EMC. |
| Other Standards | UK DfT Approved |
| SPECIFICATIONS | |
| Amblent Operating Temperature | From -10 °C to +55 °C (From +14 °F to +131 °F) |
| Humidity | 0 to 95%, no condensation |
| Protection | IP 41 (EN 60529) |
| Power Supply | AC Power: 90-264VAC/47-63Hz Battery: 12V DC Consumption: 72W Fuse: T2A 5x20 mm Power cord length: 2.5 m (8.2 ft) Automatic adjustment, without manual intervention, for power fluctuations over the voltage range of 90 to 264V AC. |
| Alarm | Audible/visible alarm. 2 x 20 character alphanumeric display and Zone Display. Alarm relay contact. |
| Alarm Time | Adjustable |
| Sensitivity | 100 sensitivity steps in each program. |
| Zone Sensitivity Adjustment | All eight independent zones are individually adjustable (0 to 255 %) with respect to the overall sensitivity level. |
| Calibration | Automatic or manually set. An automatic sensitivity function selects the appropriate sensitivity for a specific weapon or test object. This eliminates the time consuming trial and error method. |
| Interference Suppression | Intelligent 8Z8F architecture, Digital filtering, User selectable operating frequencies |
| Warranty | Two (2) years, parts and labor |
| Self-Testing Diagnostics | User-friendly diagnostics identify fault condition. |
| Maintenance | Low maintenance costs due to self-testing diagnostics, easy access and modular electronics. |
| Network Connections | MetorNet Remote Security Monitoring System compatible (RS422 and Ethernet) |
| Shipping Weight & Volume | Total: shipping weight: 94.2 kg (207.7 lbs) shipping volume: 0.51 m3 (18.02 cu ft) Net Weight: 75.8 kg (167.1 lbs) Colls: shipping weight: 73.8 kg (162.7 lbs) shipping volume: .40 m3 (14.13 cu ft) Cross bars + electronics: shipping weight: 20.4 kg (44.9 lbs) shipping volume: 0.11m3 (3.87 cu ft) |

The **Metor 300** has received the world's first environmental certificate for walk-through metal detectors.

| APPLICATIONS | |
|--------------|---|
| Airports | Public Buildings Courthouses VIP Protection |

www.rapiscansystems.com

CUSTOMER SUPPORT SERVICES: Our team is dedicated to providing a prompt, effective and personalized response that exceeds your expectations. With spare parts inventory and skilled technicians all over the world, you can be certain Rapiscan Systems will always be prepared with a solution to address your requirements. By measuring response time, parts delivery and support status, our team embraces a customer focused philosophy to ensure continual improvement in customer support, products and services.

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice.

distributor stamp

district

MetorNet 3 Pro

Remote Security Management System

Rapisoan®

ETHERNET

An OSI Systems Company

PEOPLE SCREENING

Centralized Security

Management

Remote Monitoring &

Adjustment

MetorNet 3 Pro is a Windows based remote security management system. It enables monitoring and adjustment of all parameters of the Metor family of walk-through metal detectors from a single PC.

COLLECTS STATISTICS

MetorNet 3 Pro collects statistics from the Metor walk-through metal detectors with passenger and alarm counters. These statistics can be summarized and printed in easy-to-read reports. In addition, collected statistical information can be stored in ACCESS format into a database for further processing. The user can select whether the database is stored on a PC or on a network drive.

SAVING THROUGH RESOURCE ALLOCATION


By collecting statistics through **MetorNet 3 Pro**, it is easy to allocate personnel to the right places at the right time.

CONTROL NETWORK FEATURE

The operator receives a written message whenever there is a deviation from the original settings stored in the PC. This quickly indicates any misuse or malfunction of the gate and increases the overall security level.

EASY CONNECTIVITY

Because MetorNet 3 Pro utilizes existing Ethernet cabling at the customer's premises, adding new Rapiscan Systems Metor metal detectors to the MetorNet 3 Pro network is very easy. The need for expensive cabling is minimized thus reducing costs.



ENHANCED USER INTERFACE


- All parameters of the topology can be controlled
- An image of each metal detector is shown
- Pop-up menus
- Built-in help system
- Colors can be configured on the topology

OVERALL SYSTEM MANAGEMENT

Up to 255 metal detectors can be connected to one network. The gates can be grouped and identified individually and/or by group name. The user can define the security level (set of parameters), which can be applied to an individual gate, to a group of gates, or to a whole network.

SUPERIOR SYSTEM SECURITY

MetorNet 3 Pro has two user levels: USER and SUPERUSER. The SUPERUSER has access to all parameters and can assign editable USER access rights. Each USER/SUPERUSER can have an individual password to prevent unauthorized access. The amount of USER/SUPERUSER accounts is unlimited. MetorNet 3 Pro also provides Log in and Log out data.



APPLICATIONS

MetorNet 3 Pro offers an easy way to manage one or several gates through a single PC in the following applications;

Airports

Prisons

Industry

Amusement Parks

Financial Institutions

Special Events

Distribution Centers

Government Buildings



An OSI Systems Company

MetorNet 3 Pro

Remote Security Management System

PEOPLE SCREENING

USA, CANADA, LATIN AMERICA 8 Commerce Way Suite 1.15 Robbinsville, New Jersey 08691 UNITED STATES of AMERICA Tel: +1 609-406-9000 Fax: +1 609-530-0842 Toll Free: 1-800-963-8676

AMERICAS

2805 Columbia Street Torrence, California 90503 UNITED STATES of AMERICA Tel: +1 310-978-1457 Fax: +1 310-349-2491

EUROPE, AFRICA, MID EAST Nihtisiliankuja 5, P.O. Box 174 FIN-02631 Espoo

FINLAND Tel: +358 9 32941500

Fax: +358 9 32941302 X-Ray House Bonehurst Road Salfords

Surrey RH1 5GG

UNITED KINGDOM Tel: +44 (0) 870-7774301 Fax: +44 (0) 870-7774302

ASIA

240 Macpherson Road #06-04 Pines Industrial Building Singapore 348574 SINGAPORE

Tel: +65-6743-9892 Fax: +65-6743-9885

AUSTRALIA


Rapiscan House 4 Ross Street South Melbourne Victoria Australia 3205 AUSTRALIA

Tel: +61 3 9929 4601 Fax: +61 3 9929 4655


E-MAIL

sales@rapiscansystems.com

ISO 9001:2000 Certified



LOGIN SCREEN



TOPOLOGY

| SYSTEM REQUIREMENTS | | |
|---------------------|----------------------------|--|
| Processor CPU | Pentium 4 2GHz or higher | |
| Memory | 256 MB Ram | |
| Operating System | Windows 2000 or Windows XP | |
| Hard Drive | 1-2 GB minumum | |

www.rapiscansystems.com

CUSTOMER SUPPORT SERVICES: Our team is dedicated to providing a prompt, effective and personalized response that exceeds your expectations. With spare parts inventory and skilled technicians all over the world, you can be certain Rapiscan Systems will always be prepared with a solution to address your requirements. By measuring response time, parts delivery and support status, our team embraces a customer focused philosophy to ensure continual improvement in customer support, products and services.

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice.

distributor stamp

tos (setta)

Can you see what they're hiding?



Millimeter Wave Object Detection and People Screening System

Brijot

Is it practical to screen everyone that enters—or exits—your facility, without

affecting the efficiency of your operations?

Do you know what your visitors, workforce, passengers, or spectators, are concealing past your metal detectors, bringing onto your transit system, into your stadiums, or are taking out the door with them? Is your security staff forced to guess who is hiding something without stopping and questioning each one? The Brijot BIS-WDS® GEN 2 System will allow you an easier way to know who to search and pinpoint where to look!

Brijot Imaging Systems, Inc. is proud to introduce the BIS-WDS® GEN 2—the next generation cutting edge object detection and people screening technology. System features include full-motion, real-time passive millimeter wave imaging capabilities. Empowering you to detect concealed threats sooner, minimize loss prevention more effectively, and virtually pat down and screen people in areas that you have not been able to search them before.

- Monitored remotely
- In real time
- · Without requiring cooperation
- · Without a physical pat down

Brijot's standoff passive millimeter wave imaging system offers security and loss prevention officials a quick and discrete method for detecting suspicious hidden items... whether they're explosives, weapons, contraband, stolen electronics, or other items. The GEN 2 also reveals hidden liquids and gels. Brijot's millimeter wave imaging solution is the most effective high-throughput people screening system available today to effectively detect these potential threats.




What is the BIS-WDS® GEN 2?

Brijot's GEN 2 technology is composed of a real-time Radiometric Scanner that images electromagnetic millimeter wave energy, an integrated full-motion video camera, on-board computer, and sophisticated, intelligent video detection engine. Using the GEN 2 value-added detection engine's capability your security screeners will automatically be alerted and can easily pinpoint concealed objects without intrusive, time-consuming, personnel-intensive and potentially dangerous physical searches, while allowing security screeners and law enforcement officers to perform "virtual" pat downs from a distance without direct contact. Brijot provides an effective means to manage threats before they become harmful incidents.

How does it work?

The system's **passive** Radiometric Scanner can detect concealed objects by distinguishing between the millimeter wave energy naturally emitted by the human body and the energy of the concealed objects even when they're hidden beneath clothing. It accomplishes this without radiating subjects, or posing health risks even to those persons with pacemakers, or pregnant women. Deployed as an stand-off application it will not cause claustrophobia and is a safe and discrete screening solution for all. Further, Brijot's millimeter wave sensors do not image anatomical details, thus protecting passenger privacy.



- · Detects concealed objects in as little as 0.5 second
- Subjects walk through the screening area when deployed in two-camera configurations
- Anatomical details are not revealed thereby eliminating personal privacy issues
- Completely passive system—no transmission of radiation or energy of any kind
- Seamless integration facilitating remote operation and administration of man-traps
- Monitoring & detection displayed to the operator in real-time
 Provides standoff detection of large explosives,
 Inquids, gels, and other ferrous and non-ferrous items.

Used alone or as part of a comprehensive, multi-layered security solution, choose Brijot's proven reliability to achieve your security goals. Deploy the system as part of a high-security entrance portal, integrate it with existing devices such as X-Ray or metal detectors and find the items they are missing. Or use the GEN 2 to monitor your

exits—you can even remotely image unattended locations. The GEN 2 is a must for any place where protection of life or loss prevention demands knowing which people are concealing hidden items—and pinpoint where they're hiding them.

Standoff Bomb and Weapon Detection: Protection from the threat. There is no need to put security staff or military personnel at arm's length from danger in high risk areas. Operated remotely, the GEN 2 can detect explosives or weapons and trigger a "lockdown" event, holding the suspect within a secure area. In today's high security environment, Brijot's imager adds an extra layer of protection, isolating the threat and alerting security personnel that a potential danger is approaching.

Airport/High Security Transportation Hubs: See what you're missing! Some locations—like airports and other critical transportation hubs, have already invested in security screening technologies like X-ray machines, metal detectors, and added security staff. But those technologies can't see explosive materials, liquids and gels, or thick packets of currency. GEN 2 can be integrated into your existing security


strategy, and by imaging subjects in motion, it can be used to direct subjects into secondary screening lanes for further investigation, focusing security efforts and eliminating profiling or ineffective random screening.


Government Buildings/High-Security Hotels: Broaden counterterrorism measuresi Terrorism is one the greatest threats to the safety and security of public and private buildings such as federal office buildings, hotels and many national icons. The best defense to safeguard your facility, organization and operations is "detection" that enables an immediate "assessment" for the proper "reaction." With Brijot's GEN 2 millimeter wave technology you have full-motion, real time imaging capabilities which allow you to safeguard property and lives effectively. GEN 2 can be positioned at a distance from security personnel and operated remotely to protect them from the threat posed by suicide bombers.

Loss Prevention: Stem the tide of product shrinkage! Loss prevention personnel will find the GEN 2 invaluable in identifying hidden objects exiting a facility. The system can image metals, wood, electronic devices, bottles of liquor... even fresh or frozen foods! Managers and security personnel can pat down employees virtually without physical contact. Event logging functionality records the detection, providing ideal documentation in the event of an employee termination or theft prosecution.

Graphical User Interface

How easy is it to use? Brijot's Graphical User Interface (GUI) is a simple, easy to understand tool for all operators—you can identify hidden objects without confusion or delay. With minimal training, a GEN 2 user can clearly identify and locate hidden objects in real-time by observing event icons and detection boxes on a full-motion video images. Each event's video and passive millimeter wave images are digitally archived for later review, analysis, or evidentiary use. The JPEG images stored are millimeter wave images with no anatomical detail, ensuring personnel privacy is maintained.






Loss Prevention Application Detection: Circuit Board

Real-time Detection Engine

What's that they're hiding? Know sooner with our value added detection engine, which identifies threats and concealed items on a subject in real-time—in as little as 0.5 second. The GEN 2 automatically alerts operators to the presence of very large objects—such as bombs—that could pose a serious threat. Indicator boxes pinpoint the precise area of hidden objects on the full-motion video and millimeter wave images. Displaying multiple detection events simultaneously, detection events can also serve as the "probable cause" that triggers secondary inspection events to examine an individual more closely.

Integration

What about my current systems? Good security often requires a multi-layered approach, incorporating a range of tools and carefully planned protocols, and the GEN 2 is designed to integrate seamlessly with other security systems. Each system has multiple inputs and outputs, and data can be accessed using the system's Application Programming Interface (API), allowing the Brijot system to work in tandem with your existing or planned security technologies. Brijot's system can be configured to trigger a "mantrap" application, locking out, or locking in individuals until you can identify what they're hiding.



Functional Considerations

Standard deployment: Indoor and outdoor environments. Some indoor settings and all outdoor deployment may require environment altering as specified by certified implementation personnel.

indoor deployment considerations: Ambient air temperature not to regularly exceed 26° C (80° F). Anomalous heat sources behind walls and beneath floors. Sources of energy including sky access and reflective interior surfaces.

Other deployment considerations: Traditional CCTV deployment considerations apply. Minimize saturation – Avoid facing system directly into sunlight (CCTV camera consideration) or at the sky (millimeter wave system component consideration). Though the radiometer can operate in low- or no-light settings, the integral CCTV component requires lighting the FOV for effective video imaging.

Features

Imaging capabilities: Metals, plastics, ceramics, composites, glass, liquids, gels, explosives, weapons, currency, tobacco goods, and wood-including those commonly used to construct weapons and explosive devices.

Minimum object size: Imaged pixel size: Approximately 5 cm x 5 cm (2 in x 2 in). Detection engine optimization: Approximately 7.6 cm x 12 cm (3.0 in x 5.0 in)

Large object detection: Program system's detection engine to treat identification of large objects differently. Use system's alarm utility to configure and trigger specific actions upon detection.

Simultaneous processing: Detection engine processes multiple simultaneous detections. GUI displays up to 3 detection or "Large Object" icons at a time and features a contiguous running event log.

Fully-integrated on-board computer: Pentium®-based processor enables stand-alone operation without external PC connection. Microsoft Windows XP™ Operating System integrates with local area networks for remote viewing and control via GEN 2 Application Software and APIs.

Anti-tamper software: Applications actively prevent, detect and react to tampering and reverse engineering. Imaging speed: MMW radiometer 4 to 12 frames per second (FPS); CCTV 30 FPS

Detection engine indications: Tri-colored box over location of detection on subject video image. Detection box features a black outside line, a white middle line and one of the following colors as the Inside line, determined by the user-defined detection settings: Blue: D2 level detection (warning)
 Yellow: D1 level detection (alarm)
 Red: L large object detection

A corresponding tri-colored box also appears on the "Detection Status" area of the GUI with "D1," "D2 "or "L" detection status icons.

Specifications

Power supply: External Supply, 100 to 240 VAC, 47-63 Hz, 120 W; output 12 VDC, 10 A

Detector millimeter wave frequency: 80 to 100 GHz (90 GHz center frequency, 20 GHz bandwidth)

Operating temperature: -10°C to 50°C (14°F to 122°F)

Operating humidity: 0 to 100% RH condensing (outdoor use)

Dimensions (H x W x D): 83.8 cm x 34.5 cm x 34.9 cm (33.0 in x 13.5 in x 13.7 in) excluding mounting bracket

Weight: Net: approx. 39 kg (86 lbs) - excluding mounting bracket

Interfaces

Analog video output: NTSC or PAL, BNC connector

Monitor output: D-sub 15 (VGA) connector (1024 x 768 72 Hz default)

Control, setup and monitoring: 10/100 Ethernet, RJ45

Peripheral Interface: Two USB 2.0; two IEEE 1394a (FireWire)

Keyboard/Mouse: Combined PS/2-type mini-DIN connector

Discrete I/0: 10 Position Phoenix™ connector; three user-defined outputs (dry contact Form C relay) and two user-defined inputs (opto-isolated)

Audio: One 3.5 mm jack for LINE OUT; one 3.5 mm jack for MIC IN

Innovative Detection/ **Screening Solutions**

Everyday, Brijot's cutting edge object detection/people screening system offers unsurpassed technology meeting security challenges in high threat environments. Brijot combines innovative engineering, quality materials, workmanship, outstanding customer service, and competitive pricing to bring you exceptional value. Brijot is a privately held USA Company, with corporate and training offices in Orlando, Florida. Brijot manufactures its system in an ISO 9000:2000 certified environment-another reason to select Brijot.

Brijot Imaging Systems, Inc.

5422 Carrier Drive, Suite 107 Orlando, FL 32819

Phone: 1-407-641-4370

1-866-SAFERWORLD

1-407-351-9455 Fax:

info@brijot.com Email:

Internet: www.brijot.com



Imaging a safer world®

Security Revolving Doors Large Diameter Revolving Doors



Crane Revolving Doors

Feel secure with Crane

Crane's Security Revolving Door offers the building team a perfect combination of everyday functionality and rigorous access control. Our time-tested designs and manufacturing processes—along with an unwavering dedication to quality—provide doors that meet modern demands for security and aesthetic beauty.

Control in an unpredictable world

Security needs differ from entrance to entrance, from building to building. Our Security Revolving Doors deliver exceptional control for offices, retail stores, hotels, government facilities and other applications.

Our doors can be configured to provide two-way or oneway (exit only) controlled access. You can customize settings depending on the time of day, for example, offering standard automatic or manual operation during the day and security at night. You can select custom dimensions—anything from 6'-0" I.D. to 10'-0" O.D. with maximum heights from 7'-0" to 9'-6" depending on width. In addition, Crane's patented Bookfold Collapse Lock prevents unauthorized activation of bookfold mechanism while maintaining all code criteria for revolving entrance doors.

Brains behind the brawn


Crane's Security Revolving
Doors can be integrated
with a variety of activation
devices-such as card
readers, keypads, and
sensors to enable or deny
entry. Floor mats detect
unauthorized use, preventing
entry and triggering a voice
announcement of security
violation. Safety is provided
by back pressure sensing
and edge strip protection
at the quarter posts.

Security functions can be programmed to fit your custom needs. A 90 V.D.C. motor power drive unit in the door offers reliable and controlled rotation according to your security needs. A 12° or 18° minimum canopy height is required to house power units and security components.

Secure and attractive at the same time

Bullet resistant and blast resistant, Crane's Security Revolving Doors benefit from robust engineering and material selection to render a door that works as good as it looks. Heavy-duty metals and painstaking assembly make our doors ideal for big city applications, government buildings and other structures where additional security is desired.

Stainless steel and bronze (satin or mirror finish or custom) finishes are fully welded to a formed, welded heavy gauge stainless steel or steel subframe that allows unparalleled strength in Crane doors. Aluminum finishes (anodized or painted finish) are welded and mechanically finished. Crane's experienced engineers and craftsmen will help you design a door that meets your aesthetic requirements, too. Various options and attachment configurations allow you to create a visually striking entryway that complements your building's design and is secure.





Large Diameter Revolving Doors that deliver big benefits

For six decades, architects and building owners have relied on Crane to provide the industry's most reliable and aesthetically pleasing revolving doors. That reputation for quality and excellence has been incorporated into our Large Diameter Revolving Doors.

Available in three- and fourwing configurations, Crane's Large Diameter Revolving Doors are ideal for hospitals, extended-care facilities, grocery stores, high-volume retail stores, hotels and other high-traffic applications where large objects accompany people through entryways and automatic revolving door action is desired.



Large Diameter Revolving Doors from Crane can be sized to an outside diameter up to 12'-0" in custom heights depending on the opening. They require a 12" minimum canopy fascia.

Like all Crane doors, these are built to withstand years of heavy traffic. We start with a heavy gauge stainless steel or steel subframe to ensure sturdiness throughout the life of the door. Finish options of stainless steel, bronze (satin or mirror finish or custom) and aluminum (anodized or painted finish) are welded to ensure long-term durability. Your design options are

Hyatt Hotel, Detroit, Michigan.

virtually limitless. Our artisan assemblers will customize the door's finish to your exacting specifications.

Select from an assortment of accessories and custom configurations to create a door that matches the originality of your design.

Good looks are just the beginning

Large Diameter Doors from Crane can include our patented Bookfold Collapse Lock, which prevents bookfolding during high winds or stack conditions unless an alarm is triggered. Additionally, safety detection devices are used in accordance with ANSI/BHMA A156.27-2003.

Doors can be set up and operated in continuous rotation or in response to push plates or motion sensors that will activate or slow door rotation, depending on the need. For added safety, we use

horizontal muntins instead of push bars to create two divided lights and eliminate a catch hazard.

Our Large Diameter Revolving Doors use Crane's robust power drive unit with a 90 V.D.C. motor to rotate the door and control its speed. It is engineered to provide steady, dependable door motion.

Leading the world in technology, style and performance

Crane has more than 60 years of experience designing, fabricating and installing revolving doors worldwide. We've earned our reputation as the nation's leading supplier of revolving doors by consistently delivering outstanding performance and aesthetic beauty.

In the hands of the craftsmen at Crane, metal and glass are worked into something more than revolving doors. These materials become a bold visual statement that reflects each architect's unique vision and becomes the focal point of any building.

Engineers at Crane have perfected operating hardware that ensures smooth and reliable operation. Features such as our heavy-duty bookfold mechanism offer safety that meets or exceeds national standards.

Built with painstaking attention to detail, our custom revolving doors meet your most demanding specifications. From the first revolution to the millionth, you can depend on Crane to provide the ultimate in revolving door function and quality.

Crane Security and Large Diameter Revolving Doors have provided years of reliable performance on buildings worldwide, including:

- Retail stores
- Hotels
- Government structures
- Institutional buildings
- Hospitals and healthcare facilities
- Commercial buildings
- Restaurants
- Sports stadiums

Guarantee

One year on all parts except glass. Three years on doors installed by a Crane factory authorized installer and serviced annually by a Crane factory representative. Excluding glass and normal wear on weathersweeps and push bars.

Crane Revolving Doors 924 Sherwood Drive Lake Bluff, IL 60044 Phone: 800.942.7263 or 847.295.2700 Fax: 847.295.5288 www.cranedoor.com sales@cranedoor.com

J. J SHLUSIC-

A DORMA Group Company
© 2004 Crane Revolving Doo
Company, Inc
Printed in U.S.A.